Southwest Division Naval Facilities Engineering Command Contracts Department 1220 Pacific Highway, Building 127, Room 112 San Diego, California 92132-5190

CONTRACT No. N68711-04-D-1104 CTO No. 0003

FINAL

GROUNDWATER SAMPLING REPORT, UNDERGROUND STORAGE TANK SITE 14121

Revision 0 July 26, 2005

MARINE CORPS BASE CAMP PENDLETON, CALIFORNIA

DCN: SES-TECH-05-0091

Prepared by:

SES-TECH

18000 International Boulevard, Suite 1009 Seattle, WA 98188

Tania Turpijn-Keasler
Project Geologist

Mark Cutler, P.G., C.HG. Project Manager MARK CUTLER

TABLE OF CONTENTS

<u>PAGE</u>
LIST OF TABLESii
LIST OF FIGURESii
ABBREVIATIONS AND ACRONYMSiii
.0 INTRODUCTION1-1
1.1 SCOPE OF WORK1-1
1.2 SITE IDENTIFICATION1-1
2.0 GROUNDWATER SAMPLING2-1
2.1 WATER LEVEL MEASUREMENTS2-1
2.2 SAMPLING METHODOLOGY2-1
2.3 SAMPLE ANALYSES2-2
2.4 WASTE MANAGEMENT
3-1 GROUNDWATER MONITORING RESULTS
3.1 GROUNDWATER FLOW DIRECTION
3.2 ANALYTICAL RESULTS
4-1 QUALITY ASSURANCE AND QUALITY CONTROL4-1
5.0 SUMMARY5-1
5.0 REFERENCES6-1
APPENDICES
Appendix A Well Sampling Logs
Appendix B Non-Hazardous Waste Manifest
Appendix C Laboratory Analytical Reports and Chain-of-Custody Forms

LIST OF TABLES

Table 2-1	Summary of Water Level Elevations UST Site 14121, MCB Camp Pendleton CA
Table 3-1	Summary of Groundwater Sampling Results UST Site 14121, MCB Camp Pendleton, CA

LIST OF FIGURES

Figure 1-1	Site Location Map
Figure 2-1	Groundwater Gradient and Contaminant Concentration Map (June 2005), UST Site 14121

ABBREVIATIONS AND ACRONYMS

amsl above mean sea level bgs below ground surface

BTEX benzene, toluene, ethylbenzene, and total xylenes

CTO Contract Task Order

DEH Department of Environmental Health

EPA U.S. Environmental Protection Agency

ft/ft feet per foot

LCS laboratory control sample

LCSD laboratory control sample duplicate

MCB Marine Corps Base

MCL maximum contaminant level

mg/kg milligrams per kilogram

mg/L milligrams per liter

μg/L micrograms per liter

MS/MSD matrix spike/matrix spike duplicate

MTBE methyl tert-butyl ether

PAH polynuclear aromatic hydrocarbon

RWQCB Regional Water Quality Control Board

SPLP synthetic precipitation leaching procedure

TPH-d total petroleum hydrocarbons quantified as diesel

TPH-g total petroleum hydrocarbons quantified as gasoline

UST Underground Storage Tank

VOC volatile organic compound

WQO water quality objective

1.0 INTRODUCTION

This Groundwater Sampling Report, prepared by SES-TECH, a joint venture between Sealaska Environmental Services LLC and Tetra Tech FW, presents the results of groundwater sampling completed in June 2005 at Underground Storage Tank (UST) Site 14121 at the Marine Corps Base (MCB) Camp Pendleton, California. This groundwater sampling event was conducted in response to a request from the Regional Water Quality Control Board (RWQCB) in a letter dated November 30, 2004 (reference: SMC:50-9293.05:peurp) for one additional round of groundwater sampling before site closure could be determined. The groundwater sampling activities conducted at the site, as well as the associated reporting activities, were performed under Contract Task Order No. 0003 for the Southwest Division, Naval Facilities Engineering Command Indefinite Delivery/Indefinite Quantity Contract No. N68711-04-D-1104.

1.1 SCOPE OF WORK

Groundwater monitoring at UST Site 14121 included measuring water levels and collecting and analyzing groundwater samples. During the June 2005 sampling event, all wells at the site (four wells) were sampled. As requested by the RWQB in the November 30, 2004 letter, the samples were analyzed for total petroleum hydrocarbons quantified as gasoline (TPH-g), total petroleum hydrocarbons quantified as diesel (TPH-d), benzene, toluene, ethylbenzene, total xylenes (BTEX), methyl tert-butyl ether (MTBE), and polynuclear aromatic hydrocarbon (PAHs).

1.2 SITE IDENTIFICATION

Site identification data:

Site Address: Building 14121, 14 Area, MCB Camp Pendleton

Facility Name: Logistics Modernization Team Offices

RWQCB Case No.: 9UT3293 **DEH Case:** H05939-250

Responsible Party: United States Marine Corps

Contact Person: Mr. Chet Storrs

Assistant Chief of Staff, Environmental Security

Building 22165, Box 555008

MCB Camp Pendleton, California 92055-5008

(760) 725-9774

2.0 GROUNDWATER SAMPLING

The following sections summarize the June 2005 sampling activities conducted at UST Site 14121.

2.1 WATER LEVEL MEASUREMENTS

Prior to groundwater sampling, the depth to water and the total well depth for each well were measured and recorded on a well sampling log (Appendix A). The depths were measured from the top of the well casing. Table 2-1 provides a summary of current and historical groundwater elevation data. During measurement of the water levels an obstruction was encountered in well MW3, and as a result the total depth was recorded as 11.88 feet below the top of casing (btoc), although well construction diagrams indicate that the total depth of the well is approximately 24 feet bgs. A groundwater elevation contour map was prepared based on the most recent recorded water levels (Figure 2-1).

2.2 SAMPLING METHODOLOGY

On June 1, 2005, all monitoring wells (MW1, MW2, MW3, and MW4) were sampled using low-flow sampling methodology.

Before sampling, a bladder pump was slowly lowered into each well and positioned near the center of the screen interval. The pump in well MW3 was placed below the top of the screen one foot above the obstruction. In addition, a water level indicator was placed at the water surface to monitor water-level drawdown during purging. While purging at the lowest operational setting of the pump, which was approximately 100 to 110 milliliters per minute, the water level surface began to drop and exceeded the minimum drawdown requirement of 0.33 feet in wells MW2, MW3 and MW4. The drop in water level is likely attributed to the low transmissivity of the aquifer materials.

Because a stabilized water level could not be achieved, even at very low pumping rates, a passive or minimum purge sampling method was performed following the methodology presented in a U.S. Environmental Protection Agency (EPA) Groundwater Issue paper titled *Low Flow (Minimal Drawdown) Ground-Water Sampling Procedures* (Puls and Barcelona, 1996). The passive/minimal purge approach requires the removal of a minimum of three volumes of the sampling system from each well. The liquid volume of the sampling system consists of the volume of the pump's bladder, discharge tubing and flow through cell attached to the water quality meter. After purging the required volume at the lowest flow rate achievable for each well, a groundwater sample was collected. To monitor groundwater conditions during purging, water-quality parameters were measured as follows: temperature, pH, electrical conductivity, turbidity, dissolved oxygen, and oxygen/reduction potential. These measurements were recorded

on the well sampling logs provided in Appendix A. Non-disposable downhole equipment, such as the pump and water-level indicator, were decontaminated between wells.

Groundwater samples were collected through new dedicated polyethylene discharge tubing, which was connected to the bladder pump. Each sample was collected in the appropriate containers, labeled, and placed in a cooler with ice immediately after sample collection for delivery to the analytical laboratory.

2.3 SAMPLE ANALYSES

Groundwater samples were sent to EMAX Laboratories (EMAX) for analysis of TPH-g and TPH-d using U.S. Environmental Protection Agency (EPA) Method 8015B, analysis of BTEX and MTBE by EPA Method 8260B, and analysis for PAHs by EPA Method 8270C.

2.4 WASTE MANAGEMENT

All equipment decontamination water and groundwater generated from well purging and sampling were temporarily contained in a polyethylene tank at the site and later transferred to a liquid storage tank located at the project trailer (21 Area, MCB Camp Pendleton). The tank was closed, marked, labeled, and located to minimize traffic hazards and discourage tampering. The wastewater was transported off site for disposal at a waste-permitted facility. The handling, management, transportation, and disposal of wastewater were conducted in accordance with state and federal laws and regulations. No wastes were stored at the site for more than 60 days. A copy of the waste manifest is provided in Appendix B.

3.0 GROUNDWATER MONITORING RESULTS

Groundwater flow and analytical results from the June 2005 sampling event are discussed in the following subsections.

3.1 GROUNDWATER FLOW DIRECTION

Groundwater elevations, as measured in June 2005, are presented in Figure 2-1.

As shown on Figure 2-1, groundwater elevations at the site ranged from 285.46 feet above mean sea level (amsl) at MW4 to 288.84 feet amsl at MW3. Based on water levels measured in June 2005, groundwater is flowing toward the southeast with an approximate gradient of 0.03 feet per foot (ft/ft).

3.2 ANALYTICAL RESULTS

A total of seven groundwater samples (including a field duplicate, a trip blank, and an equipment rinsate sample) were collected during the June 2005 event and sent to EMAX Laboratories for analysis. The analytical results were successfully uploaded to the RWQCB Geotracker database (Confirmation No. 6691972613). A summary current and historic groundwater sampling results is presented in Table 3-1.

TPH-g and MTBE were not detected in any of the monitoring wells.

TPH-d was detected in each of the wells at concentrations ranging from 0.21 to 1.1 mg/L. The maximum level of TPH-d (1.1 mg/L) was detected in well MW1, located adjacent to the former tank cavity.

Benzene was detected in wells MW1, MW2 and MW4 below the laboratory reporting limit (trace) at concentrations ranging from 0.32 to 0.46 $\mu g/L$. Toluene was only detected in MW1, at a trace concentration of 0.24 $\mu g/L$, and total xylenes were detected in wells MW1 and MW2 at trace concentrations of 0.36 $\mu g/L$ and 0.59 $\mu g/L$, respectively. Ethylbenzene was not detected in any of the wells.

PAH analysis resulted in the detection of trace concentrations of acenaphthene (0.88 μ g/L), acenaphthylene (0.24 μ g/L), and flourene (0.27 μ g/L) in well MW1. WQOs have not been established for these constituents. PAHs were not detected in wells MW2, MW3, and MW4.

Copies of the analytical laboratory reports and chain-of-custody forms are provided in Appendix C.

4.0 QUALITY ASSURANCE AND QUALITY CONTROL

This section summarizes the quality assurance and quality control (QC) results for the June 2005 groundwater monitoring event.

All groundwater samples were collected and preserved in accordance with the *San Diego County DEH Site Assessment and Mitigation Manual 2005* (DEH, 2005), and were delivered to the analytical laboratory within 24 hours of sample collection by a laboratory courier and analyzed within the method-specified analytical holding times. EMAX Laboratories, Inc., a state of California-certified and Naval Facility Engineering Service Center evaluated laboratory, performed sample analyses.

One field duplicate sample was collected from monitoring well MW1 (identified as 0003-007). The analytical results for the duplicate sample correlated well with the primary sample results (identified as 0003-006). The relative percent differences (RPDs) for detected target analytes such as TPH-d, benzene, acenaphthene, acenaphthylene, and fluorene ranged from 0 to 28 percent indicating an excellent agreement between the field sample and its duplicate.

To assess potential cross-contamination of BTEX and MTBE during sample transport, one trip blank sample (identified as 0003-001) was sent along with groundwater samples to the laboratory and analyzed for BTEX and MTBE. In addition, one equipment rinsate sample was collected (identified as 0003-002) to assess potential cross-contamination of BTEX, MTBE, TPH-d, and PAHs from equipment used for sampling. Detectable levels of target analytes were not reported above half the project reporting limits (RLs) in either the trip blank or the equipment rinsate sample indicating the effectiveness of sample transport and of the decontamination procedure yielding no cross-contamination during this sampling event.

In accordance with analytical method specifications, method blanks, surrogate spikes, laboratory control samples (LCSs), and duplicate LCSs were analyzed to assess method accuracy and precision.

No detectable levels of target analytes were found in the method blanks during this event. Percent recoveries in LCS, LCD, and surrogates and RPDs between the spiked duplicates were well within the project-specified QC acceptance limits. One of the LCSs for acenaphthene and acenaphthylene were recovered slightly lower than the project QC acceptance limits. The acceptable second LCS recoveries indicated method control.

In accordance with the SAP (SES-TECH, 2005), Laboratory Data Consultants, Inc., a third-party validation company, located in Carlsbad, California, performed EPA Level III/IV validation of analytical data. For this sampling event, 1 sample was validated according to the EPA Level IV protocol, and 6 samples (including field QC samples) were validated according to the EPA Level III protocol. The validation reported that all of the applicable criteria were met for all of the

samples with few minor exceptions. Data validation reported only minor discrepancies, which resulted in "J" qualifiers (estimated value) applied to some of the analytical results.

5.0 SUMMARY

The analytical results for the June 2005 groundwater sampling event were successfully uploaded to the RWQCB Geotracker database (Confirmation No. 6691972613). During the June 2005 sampling event TPH-d was detected in each of the four wells at UST Site 14121 at concentrations ranging from 0.21 mg/L to 1.1 mg/L. TPH-g and MTBE were not detected, and one or more of benzene, toluene, and total xylenes were reported at trace concentrations in wells MW1, MW2, and MW4. Low concentrations of three PAHs were also detected in well MW1, but were non-detect in wells MW2, MW3, and MW4.

As indicated in a letter dated November 30, 2004 (SMC:50-3293.05:peurp) the RWCQB had concerns about the site and requested this groundwater sampling event be completed before considering site closure. As listed in the RWCQB letter, the concerns included 1) possible effects of residual soil contamination left on-site after soil excavation, 2) possible changes in the physical or chemical equilibrium at the site during the past few years, and 3) the need to provide a high degree of protection to threatened waters, including Pilgrim Creek, which is located approximately 200 feet downgradient of the site.

As summarized in Table 3-1, TPH-d was detected in groundwater during the 1997 site assessment in only one of the four monitoring wells. MW1, located adjacent to the former tank cavity, contained 1.95 mg/L of TPH-d. TPH-d was also reported in hydropunch samples collected from two soil borings (B3 and B8) located downgradient of the tank cavity (however, not as far downgradient as wells MW2 and MW4), at levels of 1.0 mg/L and 3.8 mg/L. Data from the 1997 site assessment suggested that TPH-d impacted groundwater extended downgradient from the former tank cavity approximately 90 feet. Data from subsequent groundwater sampling events completed in 1999 and 2003, however, suggested TPH-d was not present in groundwater. During the June 2005 sampling event TPH-d was again detected in MW1 (located adjacent to the former tank cavity) at 1.1 mg/L, and for the first time TPH-d was detected in the other three monitoring wells at the site at concentrations between 0.21 mg/L and 0.89 mg/L. Comparing the 1997 data to the 2005 data, the TPH-d concentration in groundwater at the former tank cavity has decreased by almost 50% (from 1.95 mg/L to 1.1 mg/L), but at the same time the plume has migrated downgradient and TPH-d is now present in relatively low levels in downgradient wells. This type of contaminant transport pattern (between the 1997 data and 2005 data) could be expected during the time after a contaminant source is removed, and may suggest residual soil contamination is not contributing to the plume in any significant way (the maximum concentration in groundwater in the source area is decreasing and the plume is migrating with natural groundwater flow).

To address the RWQCB's concern about a change in physical and chemical conditions at the site during the past few years, no significant changes were observed. Water levels are currently

slightly above their previous highest recorded levels by approximately 0.5 to 1.0 feet, and the nature of the groundwater contaminants has not changed.

To address the RWCQB's concern about the impact the TPH-d plume may have on Pilgrim Creek, the nearest surface water body, it is important to understand whether or not Pilgrim Creek is a "gaining" creek or a "loosing" creek. Most, if not all, creeks in the arid western United States, and Southern California in particular, are loosing creeks, they have water tables that slope away from the creek indicating water will move out of the creek and into groundwater (groundwater will not recharge the creek).

Based on visual observations looking from the creek bed towards the site, the creek bed appears to be approximately 5 feet lower in elevation that the former tank cavity area, and groundwater, based on current water levels, is approximately 10 feet bgs at the former tank cavity area (MW1). In addition, groundwater is decreasing in elevation toward the creek bed, and may be as much as 5-6 feet deeper by the time it reaches the creek bed. Therefore, it is believed nearby Pilgrim Creek has not been, and cannot be, impacted by TPH-d in groundwater at UST Site 14121.

In summary, even though results of the June 2005 groundwater sampling event indicate that low levels of TPH-d were detected for the first time in some of the wells, the maximum TPH-d concentration (detected at the former tank cavity area) was lower than the previous maximum result by almost 50% (1.95 mg/L versus 1.1 mg/L). In addition, since nearby Pilgrim Creek is not expected to be impacted by local groundwater, closure is again requested to be considered for UST Site 14121.

6.0 REFERENCES

- California Regional Water Quality Control Board (RWQCB). 1994. Water Quality Control Plan for the San Diego Basin (Basin Plan) 94 (amended).
- Puls R. and M.J. Barcelona. 1996. Low-Flow (Minimal Drawdown) Ground-Water Sampling Procedures. April.
- SES-TECH. 2005. Final Sampling and Analysis Plan UST Site 14121,MCB Camp Pendleton (Field Sampling Plan and Quality Assurance Project Plan, Revision 1. April 29.
- San Diego County Department of Environmental Health, Land and Water Quality Division (DEH). 2005. San Diego County Site Assessment and Mitigation Manual 2005.

TABLES

TABLE 2-1

SUMMARY OF WATER LEVEL ELEVATIONS UST SITE 14121, MCB CAMP PENDELTON, CA

Monitoring Well ID	Well Screen Interval (feet btoc)	Reference Point (toc) Elevation (feet amsl)	Date Measured	Depth to Water (feet btoc)	Groundwater Elevation (feet amsl)					
			15-Oct-97	12.88	284.62					
			19-Jan-98 ⁽¹⁾	11.97	285.53					
MW1	9.5-24.5	297.50	29-Apr-99	11.29	286.21					
			11-Feb-03	12.16	285.34					
			1-Jun-05	10.10	287.40					
			15-Oct-97	11.14	284.15					
			19-Jan-98 ⁽¹⁾	9.89	285.40					
MW2	7.5-22.5	295.29	29-Apr-99	29-Apr-99 9.56						
			11-Feb-03	285.04						
			1-Jun-05	9.12	286.17					
			15-Oct-97	13.41	284.87					
			19-Jan-98 ⁽¹⁾	11.46	286.82					
MW3	9.5-24.5	298.28	29-Apr-99	10.91	287.37					
			11-Feb-03	dry	(dry)					
			1-Jun-05	9.44	288.84					
			05-Nov-97	10.38	283.07					
			19-Jan-98 ⁽¹⁾	8.78	284.67					
MW4	9.5-24.5	293.45	29-Apr-99	8.89	284.56					
			11-Feb-03	8.95	284.50					
			1-Jun-05	7.99	285.46					

Notes:

 $(1) - Groundwater \ elevation \ measurements \ only \ recorded \ during \ this \ period, \ no \ groundwater \ samples \ were \ collected.$

amsl- above mean sea level btoc- below top of casing MCB- Marine Corps Base

toc- top of casing

UST- Underground Storage Tank

TABLE 3-1
SUMMARY OF GROUNDWATER SAMPLING RESULTS, UST SITE 14121, MCB CAMP PENDELTON, CA

					VOCs PAHs														
Well ID	Date Sampled	Sample ID	т тРН-г г	Р-Н Ы mg/L	μg/L	ந் Toluene	ந் T	ਨੂੰ Xylenes (total)	ந் N-Propylbenzene	ក្នី Naphthalene	ந் Trichloroethene	ក្នី Tetrachloroethene	표 1,2,4-Trimethylbenzene	ਲੂ 1,3,5-Trimethylbenzene	μg.L	ਸ ਨ ਮ Acenaphthene	ந் Acenaphthylene	் ந ந ி Naphthalene	ந் T Fluorene
Water (Quality Object	tives (WQOs)	$0.005^{(1)}$	$0.1^{(1)}$	1	150	680	1750	30	0.5	5	5	(2)	(2)	13 ⁽³⁾	(2)	(2)	(2)	(2)
	15-Oct-97	not listed	na	1.95			3.2	3.2	2.6	21		2.1	8.3	4.1	na			10.4	2.6
	29-Apr-99	not listed							na	na	na	na	na	na					
MW1	28-Feb-03	020314121-001	na							na	1J					na	na	na	na
	1-Jun-05	0003-006		1.1	0.41J				na	na	na	na	na	na		1.0	0.27J		0.36J
	1-Jun-05	0003-007 (Dup)		1.1	0.39J	0.24J		0.36J	na	na	na	na	na	na		0.88J	0.24J		0.27J
	15-Oct-97	not listed	na		na	na	na	na	na	na	na	na	na	na	na	na	na	na	na
MW2	29-Apr-99	not listed							na	na	na	na	na	na					
141 44 2	28-Feb-03	020314121-002	na							na	3					na	na	na	na
	1-Jun-05	0003-004		0.86	0.46J			0.59J	na	na	na	na	na	na					
	15-Oct-97	not listed	na		na	na	na	na	na	na	na	na	na	na	na	na	na	na	na
MW3	29-Apr-99	not listed							na	na	na	na	na	na					
141 44 3	28-Feb-03	well dry	na		na	na	na	na	na	na	na	na	na	na	na	na	na	na	na
	1-Jun-05	0003-005		0.26					na	na	na	na	na	na					
	05-Nov-97	not listed	na		na	na	na	na	na	na	na	na	na	na	na	na	na	na	na
MW4	29-Apr-99	not listed							na	na	na	na	na	na					
141 44 4	28-Feb-03	020314121-003	na							na						na	na	na	na
	1-Jun-05	0003-003		0.21	0.32J				na	na	na	na	na	na					
Project Rep	orting Limits	(4)	0.05	0.01	0.5	0.5	0.5	1.5	na	na	na	na	na	na	na	1	1	1	2

Notes:

Bold values exceed listed WQO

- (1)- Secondary taste and odor threshold value
- (2)- No established WQO
- (3)- California DHS proposed primary MCL
- (4)- Reporting limit listed for most recent sampling event only.

μg/L- micrograms per liter

mg/L- milligrams per liter

-- - Not detected above project reporting limits

Dup- field duplicate sample

MCB- Marine Corps Base

MTBE- methyl tert-butyl ether

na - not analyzed

PAHs- polynuclear aromatic hydrocarbons Method 8270C

VOCs- volatile organic compounds by EPA Method 8260B


TPH-g- total purgeable petroleum hydrocarbons quantified as


gasoline (EPA Method 8015B)

UST- Underground Storage Tank

WQO - water quality objective

FIGURES





APPENDIX A WELL SAMPLING LOGS

SES-TECH

Field Water Level Measurements

Date:6/1/65	Project Name: 05T 517F (412)
Personnel: Tain Turp-yn-Korsler	Project OFS: 2290.0010.0009
N. Weing onon	Measurement Device: Source 57
Weather Sun 1001	Commonto

Well I.D.	Depth to Water from Measuring Point (feet)	Depth to Sediment from Measuring Point (feet)	Comments
mWI	10.16	24.74	
mw2	9.12	22-13	
mu3	9,44	11.94	obstruction below purpe
mwy	7.99	24-07	
			· .

Pi	roject Name:	: MST s	Fite 1412	<u>-1</u>		Well Number:	····								
Proj	ject Number:	2990.00	30-0005	**************************************	nteres			nple Pro Mini	****						
Site	Date.	- 6/1/W	5 jo-kënder, Nick	- 1 /2]	map.			$\frac{\infty 6/\infty 7}{100}$	ime: JY	<u>ks //470</u>					
Oico	CHYRICG (S).	Jana (Mr. P.)	F-KEWler INICH	Wenberger	-	Contractor.	r: Tetra Tech	1 FW, Inc							
Reference	e: Top of Casi	ing	Before	After	Tol	otal Volume Po	urged (mL):	: 2,56	6						
Depth to W	Nater (ft)		10,003	10.12	Notes/Caics:										
Depth of W	• •	,	24.74	LIU.IL	(2.4.17)+470=510-8										
· ·	Гор of Screen	n		-	System Vol (mL) = (2.4*H)+470										
Screen Ler	=		9.5° 15	•	where										
Pump dept	- , .	•	~17	•	2.4mL/ft = tubing volume per foot (1/8"ID)										
Pump Rate		•	100 mym	- '''	H = length of tubing in feet										
Sample Pu			100 m/mi	<u>.</u>	4	Bladder volun	-		ume						
System Vo	olume		~510m1	-				•							
Time	рН	Conductivity (µmhos)	Dissolved Oxygen (mg/L)	Temp. (°C)	ORP (mV)	Turbidity (NTU)	Depth to Water (ft)	Cum. Volume (mL)	Comments						
1345							10.05	0	Start	Pamo					
1350	5.61	12,100	2.17	23.4	23	36.4	10.08	500	1	rooder					
1353	5.55	12,300	046	24.6	28	24.7	10,09			40000					
1400	5,57	12,400	0,25	24.2	36	32.7	1011	1300	11	ч					
1405	5.57	12,700	0.25	24.1	40	38.4	10.12		4	L!					
14/0			0.23	24.)	42	40.7	10.12	2500	7 1	c į					
1415			# 0003	-006					<u> </u>						
1420	Colleci	Sample	1 0003-		(FD)										
				. !											
<u> </u>	!														
						-									
Stability:	± 0.2 units	± 3-5%	± 0.2 mg/L	± 0.3 %	± 20 mV	± 10%	<u> </u>	<u></u> J	<u>. </u>						
Hach Fe ²⁺	Market and the second	N/A													
Samples w	vere collected	directly from	pump unless ot	therwise note	ed.										

Proje	ect Number: Date:	2990,00	ite 1412 030.000 pijn-Keaskr,	05	-	Vell Number: Equipment: Sample ID: Contractor:	QED Sam : <i>600</i> 3	nple Pro Mini - <i>ОФЧ</i> т					
Reference:	: Top of Casi	ng	Before	After	Tota	al Volume Pu	urged (mL):	3300	<u>D</u>	V			
Screen Len Pump depth Pump Rate Sample Pur	Vell (ft) op of Screen ngth (ft) th (ft) e ump Rate		9.12 22.13 1.5 15.5 110n1/nin 100n1/mo	-	Notes/Calcs: (2.4 × 23) +470 = 525.2 System Vol (mL) = (2.4*H)+470 where 2.4mL/ft = tubing volume per foot (1/8"ID) H = length of tubing in feet 470 mL = Bladder volume + Flowthru cell volume								
System Vol	pH	Conductivity (µmhos)	Dissolved Oxygen (mg/L)	Temp. (°C)	ORP (mV)	Turbidity (NTU)	Depth to Water (ft)	Cum. Volume (mL)	Cor	nments			
1137			\(\frac{1}{3} = \frac{1}{3} \)				9.08	(IIL)	Stari	Pump			
1142	6.40	12,000	3.03	22.1	180	2.1	9.20	950		10000			
1147	1	12,360	0.66	22,1	159	2-3	9.26	1100	1	·,			
1152		13,600	Q35	22.1	146	0.3	9.31	1650	٠,٤	~			
1157	1	17,500	0.28	22.1	137	0.0	9.43	2,200	ų	٠,			
1202	<u> </u>	1	0.23	22.2	131	0.CV	9.51	2,750	,.	٠,			
	6.48	18,000	0.19		128	0.0	9.56	3300		٠,			
1212		+ Sample	 	<u> </u>									
		/		-									
									<u> </u>				
Stability:	± 0.2 units	± 3-5%	± 0.2 mg/L	± 0.3 %	± 20 mV	± 10%			<u>L</u>				
	NA	_								:			
Samples we	ere collected	i directly from	pump unless of	therwise note	d.								

Proj	ect Number: Date:	2990.0	ine 1412 1430, 00 105 195 keuste	005	-			ple Pro Mini <i>- 0∕</i>						
Reference:	: Top of Casi	ing	Before	After	Tot	al Volume Pi	urged (mL):	3,00	Oul	,				
Depth to W Depth of W Depth to To Screen Ler Pump dept Pump Rate Sample Pu System Vo	Vell (ft) op of Screen ngth (ft) th (ft) ∋ ump Rate		9.32 11.88 9.5 15' 100ml/min 100ml/min		Notes/Calcs: (2.4x) + 470 System Vol (mL) = (2.4*H)+470 where 2.4mL/ft = tubing volume per foot (1/8"ID) H = length of tubing in feet 470 mL = Bladder volume + Flowthru cell volume									
Time	рН	Conductivity (μmhos)	Dissolved Oxygen (mg/L)	Temp. (°C)	ORP (mV)	Turbidity (NTU)	Cum. Volume (mL)	Comments						
1239							9.32	0	Start	Parp				
1244	6.34	451	4.77	20.822.4	-243	20.8	2.63	500	1	40000				
1249	6.24	411	0.77	22.4	-240	14.0	9.88	1000	¹ Ł	4				
1254	6-69	533	0.27	22.5	227	14.9	9.96	1300	+1	7				
1259	6.08	710	0.12	22.5	-223	14.6	1012	2000	"(Lį.				
1304	6.11	438	0.07	22.5	-224	14.2	10.28	2500	ч	Łŗ				
1309	6.14	484	0.06	22.5	-227	148	1038	3,000	P	ч				
1314	colled			0003-	005			<u></u>						
								:						
Stability:	± 0.2 units	± 3-5%	± 0.2 mg/L	± 0.3 %	± 20 mV	± 10%								
Hach Fe ^{2⁺}	NA		* pull	led pur	an an	(
Samples w	ere collected	I directly from	pump unless o	therwise note	ed.									

Proj	ect Number: Date:	2990 c	SITE 14 0083.000 05 19131- Kous	>05	•••	Sample ID	QED Sam	ple Pro Min	i Bladder Pump 'ime: // ○ ऽ					
Reference	: Top of Cas	ing	Before	After	Total Volume Purged (mL): 2,500 mL									
Depth to W Depth of W Depth to T Screen Ler Pump dept Pump Rate Sample Pu System Vo	Vell (ft) op of Screen ngth (ft) th (ft) imp Rate	i Æ	7.99 24.07 9.5 15! 16 Let' 100 ml/m. 100 ml/m. ~530 ml		Syst 2.4mL/ft = t H =	2.4 ¢25) tem Vol (mL) where tubing volum length of tu) = (2.4*H)- ne per foot bing in feet	+470 (1/8"ID)	ume					
Time	рН	Conductivity (µmhos)	Dissolved Oxygen (mg/L)	Temp. (°C)	ORP (mV)	Turbidity (NTU)	Depth to Water (ft)	Cum. Volume (mL)	Comments					
1036									PUMPON SET RA					
1041	6.00	9380	1.23	23.0	209	2.4	8.27	500	100ml/min					
1046	6.02	10,600	0.33	23. W	173	0.0	8.37	1000	1					
1051	6.04	15,200	0.23	23.0	162	0.0	8.50	1500						
1056	6.05	14,800	0.20	23.0	153	0.0	8,54	2,000						
1101	خصیصا	14,400	0.17	23,0	151	0,0	8.61	2500						
1105	Collec-		0003	-003										
		/												
			<u> </u>											
Stability:	± 0.2 units	± 3-5%	± 0.2 mg/L	± 0.3 %	± 20 mV	± 10%								
Hach Fe ²⁺	NA													
Samples w	ere collected	I directly from	pump unless o	therwise note	d.									

APPENDIX B NON-HAZARDOUS WASTE MANIFEST

NON-HAZARDOUS WASTE MANIFEST (Form designed for use on elite (12 pitch) typewriter) Manifest Document No. 2. Page 1 1. Generator's US EPA ID No. **NON-HAZARDOUS** 51160 Park. CA2170023533 οť WASTE MANIFEST 3. Generator's Name and Mailing Address Tatia Tech FM, inc. 1230 Columbia Street Suite 500 San Diogo, CA 92101 34/7 4. Generator's Phone (F-Attus Make Dolumbon US EPA ID Number A. State Transporter's ID 5. Transporter 1 Company Name 800-326-1011 General Environmental Home inc. [CAD983649880 B. Transporter i Phone LIS EPA IO Number C. State Transporter's ID 7, Trensporter 2 Company Name 8. D. Transporter 2 Phone US EPA ID Number E. State Facility's IO 9. Designated Facility Name and Site Address 30 ik knviromentai 3650 East 25th Street F. Facility's Phone 323-268-5056 [CATOBOO3368] Vernon, CA 94023 t3. Total Guantity 12. Containers 11. WASTE DESCRIPTION Νo. Type Non harmachous biquid (Moth Mator) 318 0 4 GEN b. ER Ċ. Ā 0 B H, Handling Codes for Wastes Listed Above G. Additional Descriptions for Materials Listed Above tla; 5x55g-Well Mater-Approvat#340901-24 UST SITES 14121, 14125, 1133, 43522 1210620 15. Special Handling Instructions and Additional Information
Emergency Phone: (800) 326-1011 (G.E.H.) PO#055946 16. GENERATOR'S CERTIFICATION: I hereby certify that the contents of this shipment are fully and accurately described and are in all respects in proper condition for transport. The materials described on this manifest are not subject to federal hazardous waste regulations. Date Year Signature kârentîs Onv Printed/Typed Name 17. Transporter 1 Acknowledgement of Receipt of Materials Oaks TRANSPORTER Day Year Month Signature Printed/Typed Name 10 CL 18. Transporter 2 Acknowledgement of Receipt of Materials Date Signature Month Day 1081 Printed/Typed Name 19. Discrepancy Indication Space F C

Signature

Date

Year

20. Facility Owner or Operator, Certification of receipt of the waste materials covered by this manifest, except as noted in item 19.

Printed/Typed Name

8

T.

APPENDIX C

LABORATORY ANALYTICAL REPORTS AND CHAIN-OF-CUSTODY FORMS

NUMBER

06593

1230 Columbia Street, Sunc and San Diego, CA 92101 (619) 234-8696

CHAIN-OF-CUSTODY RECORD

PROJECT NAME		PURCHASE ORD	ER NO.					l		A N	AT	VCE	c Di	E QU I	ED E	<u> </u>		LABORATORY NAME	1		·····	
VST Sine 1412	2.1	05	585	50	į			¥	1			1 (312)	T	T T	T	Ť	Т	<i>†</i>	Project Info	orm:	atini	n
PROJECT LOCATION	***************************************	PROJECT NO.		,													1	EMAX	Secti			
CAMP PLUDGE	1 () /	2500.	040B/	.00	04	1,00	w	1	-41%	TAN STATE	1	1				1/	1	Crivax	Do not su		t to	
SAMPLER NAME		SAMPLER SIG	NATURE	•		1		1	140	(3)						K	1	LABORATORY ID	Labora			
TAND TURPUN K	EVISILY	Jana	24	7.29	i jadi		OP)	_	64.	Į,		7		N		Ь		(FOR LABORATORY)			,	
PROJECT CONTACT ACIZICS ON		AIRBILL NUMBE	R 112 I C					1175	7.7	12. FOC	1000			16	1			05F010				
SAMPLE ID	. DATE COLLECTED	TIME COLLECTED	NO. OF		VEL	T Y	T A	8	6.0	\$ 15.			K					COMMENTS	LOCATION	DEI	PTH	QС
	100	COLLECTED	CONTAINER	3	4	E	T	لندة	4,4,4		-		<u></u>			<u> </u>				START	END	
0003-001	6/100	0945	3	X		W	day	X											14121	-	_	τ_{B}
0003-007	bfilos	1000	8	Α		W	ORMY.	X	χ	X				1	T				EGUAR RIMS			ER
0003-003	6/1/05	1105	8	Īχ		W	TÜ du e	X	X	X	7				T	<u> </u>					_	e _e
0003-004	6/1/05	1212	8-	Х		W		X	H	X	1	 			 	<u> </u>			14121-MW4		-	Rec
	<u> </u>			1-			10		 	 	Ľ	╂	 	┿	├	╀	 		14121-MWZ	-		
0003-005	6/1/05		8	Ľ	-	W	रे _ं		X	X	X					<u> </u>			14121-MW3		_	K € G
0003 2006	6/1/05	1412	প্ত			W	17.		<u> </u>	X	X								Misi-WMI	- Charles	-17/68	RE
0003:007	6/1/05	1420	8	X.		W).].:-j	X	X	X	7								14121-MW1	****	anie.	$F_\mathfrak{D}$
							,															
	(Q																					
	15-											T			<u> </u>							
				IJ		1	1															
RELIDIQUISHED DI (Signature)	DATE 10/1/55	RECEIVED BY IS	gnature)			LABO	OR A'	TOR	Y INS	TRI	CTIO	NS/C	OMN	I		<u>L</u>	<u> </u>		SAMPLING COMME		L	\Box
CONTRODS US - TECH	7606	COMPANY (Si				*						eorti		E.	70	Ø£	CO	NE WALD BY	QUARTERY		ن	
RELINQUISHED BY (Signature)	1000	EN	人(二)	`						•		CAUN (1							SAMP			l
second season or (signamic)	DATE	RECEIVED BY (Si	gnature) F		T	COM	POSI	TEI	DESCI	RIPT	ION							<u> </u>	3,7700170	ame fruit	(J	1
COMPANY	TIME	COMPANY																				ĺ
RELINQUISHED BY (Signature)	DATE	RECEIVED BY (Si	IVED BY (Signature)				CAMPLE CONDITION UPON DECEMPS (FOR								11.7.7.							
			L)A				SAMPLE CONDITION UPON RECEIPT (FOR LABORATORY) TEMPERATURE: SAMPLE CONDITION: INTACT								Control of the Contro							
COMPANY	TIME	COMPANY				COOI		10000			INTA	CT	131, 314	□В	1 11 11	1,377,60		☐INTACT ☐BROKEN				
	L							- 12		Ü				3.1	1000	100	14.75%	[발레이다] 그는 사회생활은 보급하다				- 1



TABLE OF CONTENTS

CLIENT:

SES-TECH

PROJECT:

CAMP PENDLETON, UST SITE 14121

SDG:

05F010

SECTION		PAGE 1000 – 1004	
Cover Letter, CO	OC/Sample Receipt Form		
GC/MS-VOA	**	2000 –	
GC/MS-SVOA	SW 3520C/8270C SIM	3000 – 3083	
GC-VOA	METHOD 5030B/M8015 METHOD 5030B/8021B	4000 - 4046 4047 - 4088	
GC-SVOA	METHOD 3520C/M8015	5000 – 5046	
HPLC	**	6000 ~	
METALS	**	7000	
WET	**	8000 –	
OTHERS	**	9000	

^{** -} Not Requested







1835 W. 205th Street Torrance, CA 90501 Tel: (310) 618-8889 Fax: (310) 618-0818

Date: 06-16-2005 EMAX Batch No.: 05F010

Attn: Sevda Aleckson

SES-TECH

1940 E. Deere Avenue, Suite 200

Santa Ana CA 92705

Subject: Laboratory Report

Project: Camp Pendleton, UST Site 14121

Enclosed is the Laboratory report for samples received on 06/01/05. The data reported include :

Sample ID	Control #	Col Date	Matrix	Analysis
0003-001	F010-01	06/01/05	WATER	BTEX & MIBE
0003-002	F010-02	06/01/05	WATER	SEMIVOLATILE ORGANICS SIM TPH DIESEL BTEX & MTBF
0003-003	F010-03	06/01/05	WATER	SEMIVOLATILE ORGANICS SIM TPH DIESEL TPH GASOLINE
0003-004	F010-04	06/01/05	WATER	STEX & MTBE SEMIVOLATILE ORGANICS SIM TPH DIESEL TPH GASOLINE
0003-005	F010-05	06/01/05	WATER	STEX & MTBE SEMIVOLATILE ORGANICS SIM TPH DIESEL TPH GASOLINE
0003-006	F010-06	06/01/05	WATER	BTEX & MTBE SEMIVOLATILE ORGANICS SIM TPH DIESEL TPH GASOLINE



Sample ID

Control # Col Date Matrix Analysis

0003-007

F010-07 06/01/05 WATER

BTEX & MTBE SEMIVOLATILE ORGANICS SIM

TPH DIESEL
TPH GASOLINE BTEX & MTBE

The results are summarized on the following pages.

Please feel free to call if you have any questions concerning these results.

Sincerely yours,

Kam Y. Pang, Ph.D. Laboratory Director

FOSTER WHEELER ENVIRONMENTAL COI		NUMBER	06593	
J3 VW (-2	CHEARN CAR CRICO	TODY RECORD	05F010	
PROJECT NAME	PURCHASE ORDER NO.	ANALYSES REQUIRED	LABORATORY NAME	
VST SITE 14121	055850	* •	7	
CAMP PENDLETON SAMPLER NAME	2990,0908,0004,0000 SAMPLER SIGNATURE	PH-9 PH-9 PH-9	EMAX	44 Edg. 1
3	SAMPLER SIGNATURE		LABORATORY ID	
TANIA TURPUN - KEASLEY	Janustupy furth		(FOR LABORATORY)	
SEVDA ALEKSON	COURIER	302.16 8 20.16 81.56	05F010	
SAMPLE ID DATE COLLECTED	TIME NO. OF LEVEL T T T CONTAINER 3 4 F T	EPA 3 EPA 8	COMMENTS	alektrise komposite († 1865) 1865 - Paris Green
0003-001 6/105	0945 3 X W 244	X	•	
0003-002 blilos	1000 8 x W 201	XXX		
0003-003 6/1/05	1105 8 x 4 204	XXXX		
0003-004 6/1/05	1212 8 X Way	$\times \times \times \times$		
0003-005 6/1/05	1314 8- X W&	XXXX	•	
6003-006 6/1/05	7	X X X X		
0003-007 6/1/05	1420 8 K W W W W	XXXX		
677			N. Company	
105				
EE MOGO				
RELINQUISHED BY (Signature) DATE 6/1/65		TORY INSTRUCTIONS/COMMENTS DETECTIONS OF MITTE TO BE O	ONFIRMED BY	
RELINOUS FED BY (Agrature) DATE		PA 50308 8260B		
COMPANY COMPAN	COMPANY	ITE DESCRIPTION	4000	
17//	RECEIVED BY (Signature) SAMPLE	CONDITION UPON RECEIPT FOR LABORAT	1002	
COMPANY TIME	TEMPERA COMPANY COOLER	CONDITION UPON RECEIPT (FOR LABORAT ATURE: 3-8-7-5 SAMPLE CONDITION: SEAL: TINTACT BROKEN	☐INTACT ☐BROKEN	
		aboratory; Canary - Project File; Manila - Data		e dia





EMAX-SM()2 Rev 3 Appendix 2

SAMPLE RECEIPT FORM I

Type	e of Delivery	Delivered By/Airbill	noul -	. 48
EMAX Courier		TAIL HATCHAR	ECN OSF	<u> </u>
Cient Delivery		The Wicethia	Recepient T. PK-	EL
Third Party				<u>-05</u>
			Time 1876	<u>O</u>
	// // // // // // // // // // // // //	COC Inspection		
Client Name		Sampler Name	Sampling Date/Time/Location	
Address		Courier Signature/Date/Time		arı.
☐ Client PM/FC		TAT	Analysis Required	
Tel #/Fax #		Sample ID	∐ Matrix □ n	
afety Issues	None	High Concentrations expected	Preservative (if any)	
omments:	Rad Screening Requir	red	Superfund Site Samples	
ontainer	[] <i>(</i> 2)	Packaging Inspection		
ondition	Coolers (2)	☐ Box	. 7	
	Custody Seat	☐ Intact ☐ Dan	iaged []	
ackaging	Bubble Pack	Styrofoam		`
emperatures	₽€00ler17:38°C	Cooler 2 -25 C		$i \in \mathcal{B}$
	Codier 5		7 Cobier 4 Cobier 8 Cooler 8	
	Cooler 9		" ' : Cooler &	
mmente:		Cooler 10 Coole		
omments:		:] Cooler 10 Coole	7 1] Cooler 12	
		:_J cooler 10 Coole		
LSCID	Client ID	Discrepancy	r 1) Cooler 12	
LSCID	Client ID	Discrepancy	r 1) Cooler 12	
LSCID	Client ID	Discrepancy	r 1) Cooler 12	
LSCID	Client ID	Discrepancy	r 1) Cooler 12	
LSCID	Client ID	Discrepancy	r 1) Cooler 12	
LSCID	Client ID	Discrepancy	r 1) Cooler 12	
LSCID	Client ID	Discrepancy	r 1) Cooler 12	
LSCID	Client ID	Discrepancy	r 1) Cooler 12	
LSCID	Client ID	Discrepancy	r 1) Cooler 12	
LSCID 05 - 028/3	Client ID	Discrepancy	r 1) Cooler 12	
LSCID	Client ID	Discrepancy	r 1) Cooler 12	
LSCID 05 - 028/3	Client ID	Discrepancy	r 1) Cooler 12	
LSCID 05 - 028/3	Client ID	Discrepancy	r 1) Cooler 12	
LSCID 05 - 028/3	Chent ID	Discrepancy	r 1) Cooler 12	
LSCID 05 - 528/31	Chent ID	Discrepancy	r 1) Cooler 12	
LSCID 05 - 528/31 ID . Lab Sample IEWS	Chent ID	Discrepancy	r 1) Cooler 12	
LSCID 05 - 028/31 ID . Lab Sample IEWS mple Labeling	Chent ID	Discrepancy HO TIME ON LABBO	Corrective Action	
LSCID 05 - 528/31 ID . Lab Sample IEWS	Chent ID	Discrepancy	Corrective Action	



REPORTING CONVENTIONS

DATA QUALIFIERS:

Lab Qualifier	AFCEE Qualifier	Description
J	F	Indicates that the analyte is positively identified and the result is less than RL but greater than MDL.
N		Indicates presumptive evidence of a compound.
В	В	Indicates that the analyte is found in the associated method blank as well as in the sample at above QC level.
E	J	Indicates that the result is above the maximum calibration range.
*		Out of QC limit.

Note: The above qualifiers are used to flag the results unless the project requires a different set of qualification criteria.

ACRONYMS AND ABBREVIATIONS:

CRDL.	Contract Required Detection Limit
RL	Reporting Limit
MRL	Method Reporting Limit
PQL	Practical Quantitation Limit
MDL	Method Detection Limit
DO	Diluted out

DATES

The date and time information for leaching and preparation reflect the beginning date and time of the procedure unless the method, protocol, or project specifically requires otherwise.



LABORATORY REPORT FOR

SES-TECH

CAMP PENDLETON, UST SITE 14121

SW 3520C/8270C SIM SEMI VOLATILE ORGANICS BY GC/MS

SDG#: 05F010



CASE NARRATIVE

CLIENT:

SES-TECH

PROJECT:

CAMP PENDLETON, UST SITE 14121

SDG:

05F010

SW 3520C/8270C SIM SEMI VOLATILE ORGANICS BY GC/MS

Six (6) water samples were received on 06/01/05 for Semi Volatile Organic analysis by Method 3520C/8270C SIM in accordance with USEPA SW846, 3rd ed.

1. Holding Time

Analytical holding time was met.

2. Tuning and Calibration

Tuning and calibration were carried out at 12-hour interval. All QC requirements were met.

3. Method Blank

Method blank was free of contamination at half of the reporting limit.

4. Surrogate Recovery

Recoveries were within QC limit.

5. Lab Control Sample/Lab Control Sample Duplicate

Recoveries were within QC limit except two analytes in LCS1W were slightly below QC but met QC in duplicate analysis.

6. Matrix Spike/Matrix Spike Duplicate

No MS/MSD sample was designated in this SDG.

7. Sample Analysis

Samples were analyzed according to the prescribed QC procedures. All criteria were met with the aforementioned exception.

LAB CHRONICLE SEMI VOLATILE ORGANICS BY GC/MS

			# # # # # # # # # # # # # # # # # # # #					***************************************	
SES-TECH CAMP PEN	SES-TECH CAMP PENDLETON, UST SITE 1412'	14121						SDG NO.	SDG NO. : 05F010 Instrument 10 - 1-052
	机线线 医乳球球 医乳球球球球球球球球球球球球球球球球球球球球球球球球球球球球球球	14	7 11 11 11 11 11	1 计分析设计 化二氯甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基					61
				-	WATER				
	Laboratory	Dilution	3-6	Analysis	Extraction	Sample	Calibration Prep.	n Prep.	
	Sample ID	Factor	Moist	Datelime	Dateline	Data FN	Data FN	Batch	Motes
	\$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	+ + + + + + + + + + + + + + + + + + + +	k k	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	6 C F F F F F F F F F F F F F F F F F F			1 1 1	* 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	SVF009WB	_	₩A	06/08/0520:01	06/06/0515:00	RFK204	RDK196	SVF009W	Method Blank
	SVF009WL	•~	NA	06/08/0520:23	06/06/0515:00	RFK205	RDK 196	SVF009W	Lab Control Sample (LCS)
	SVF009WC		ĀN	06/08/0520:44	06/06/0515:00	RFK206	RDK196	SVF009W	LCS Duplicate
	F010-02	56.	NA A	06/08/0521:49	06/06/0515:00	RFK209	RDK196	SVF009W	Field Sample
	F010-03	\$6.	¥¥	06/08/0522:11	06/06/0515:00	8FK210	RDK196	SVF009W	Field Sample
	F010-04	- 95	¥	06/08/0522:32	06/06/0515:00	RFK211	RDK196	SVF009W	Field Sample
	F010-05	76.	¥	06/08/0522:54	06/06/0515:00	RFK212	RDK196	SVF009W	Field Sample
	F010-06	.95	NA	06/08/0523:15	06/06/0515:00	RFK213	RDK196	SVF009W	Field Sample
	F010-07	66.	MA	06/08/0523:37	06/06/0515:00	RFK214	RDK 196	SVF009W	Field Sample

FN - Filename % Moist - Percent Moisture



SAMPLE RESULTS



PARAMETERS	RESULTS (ug/L)	RL (ug/L)	MDŁ (ug/L)
ACENADUTUENE	ND.	95	******
ACENAPHTHENE		. 7.3	.19
ACENAPHTHYLENE	ND	.95	.19
ANTHRACENE	ND	1.9	.19
8ENZO(A)ANTHRACENE	ND	1.9	.19
BENZO(A)PYRENE	ND	.95	.19
BENZO(B)FLUORANTHENE	ND	.95	.19
BENZO(K)FLUORANTHENE	ND	1.9	.19
BENZO(G,H,I)PERYLENE	ŃD	.95	.19
CHRYSENE	ND	1.9	.19
DIBENZO(A, H)ANTHRACENE	CM	. 95	.19
FLUORANTHENE	NO	1,9	.19
FLUORENE	NO	1.9	.19
:NDENG(1,Z,3-CD)PYRENE	NO	.95	.19
NAPHTHALENE	ND	.95	.19
PHERANTHRENE	NO	, 95	.19
PYRENE	ND	1.9	.19
SURROGATE PARAMETERS	% RECOVERY	ac Limit	
TERPHENYL-D14	70	50-130	

RL: Reporting Limit



	RESULTS	RĻ	MDL
PARAMETERS	(ug/L)	(ug/L)	(ug/L)
	* * * * * *		
ACENAPHTHENE	ND	95	.19
ACENAPHTHYLENE	NO	.95	.19
ANTHRACENE	ND	1.9	.19
BENZO(A)ANTHRACENE	ND	1.9	.19
BENZO(A)PYRENE	ND	.95	.19
BENZO(B)FLUORANTHENE	ND	.95	.19
BENZO(K)FLUORANTHENE	ND	1.9	.19
BENZO(G,H,I)PERYLENE	ND	.95	.19
CHRYSENE	ND	1.9	.19
DIBENZO(A, H)ANTHRACENE	RD	. 95	.19
FLUORANTHENE	ND	1.9	.19
FLUORENE	NO	1.9	.19
INDENO(1,2,3-CD)PYRENE	NO	.95	.19
NAPHTHALENE	MD	.95	.19
PHENANTHRENE	CN	.95	.19
PYRENE	ND	1.9	.19
SURROGATE PARAMETERS	% RECOVERY	QC LIMIT	

67

50-130

RL: Reporting Limit

TERPHENYL-D14



Client : SES-TECH Date Collected: 06/01/05 Project : CAMP PENDLETON, UST SITE 14121 Date Received: 06/01/05 Batch No. : 05F010 Date Extracted: 06/06/05 15:00 Sample ID: 0003-004 Date Analyzed: 06/08/05 22:32 Lab Samp 1D: F010-04 Dilution Factor: .95 Lab File ID: RFK211 Matrix : WATER Ext Btch ID: SVF009W % Moisture : NA Instrument ID : T-052 Calib. Ref.: RDK196

	RESULTS	RŁ.	MDL
PARAMETERS	(ug/L)	(ug/L)	(ug/L)
	* * * * * *		
ACENAPHTHENE	ND	.95	.19
ACENAPHTHYLENE	ND	.95	-19
ANTHRACENE	ND	1.9	-19
BENZO(A)ANTHRACENE	ND	1.9	.19
BENZO(A)PYRENE	ND	.95	.19
BENZO(B)FLUORANTHENE	ND	.95	. 19
BENZO(K)FLUORANTHENE	ND	1.9	. 19
BENZO(G, H, I)PERYLENE	NO	.95	.19
CHRYSENE	ND	1.9	.19
DIBENZO(A, H)ANTHRACENE	ND	. 95	.19
FLUORANTHENE	ND	1.9	. 19
FLUORENE	ND	1.9	.19
INDENO(1,2,3-CD)PYRENE	ND	.95	.19
NAPHTHALENE	ND	.95	.19
PHENANTHRENE	ND	.95	. 19
PYRENE	ND	1.9	.19
SURROGATE PARAMETERS	% RECOVERY	QC LIMIT	

50-130

RL: Reporting Limit

TERPHENYL-D14



%5457X4082**735884444**

**************************************	12422222222222222222	*****	
	RESULTS	RL	MDL
PARAMETERS	(ug/L)	(ug/L)	(ug/L)
	/ n = n = w		
ACENAPHTHENE	ND	94	. 19
ACENAPHTHYLENE	NO	.94	.19
ANTHRACENE	ND	1.9	.19
BENZO(A)ANTHRACENE	ND	1.9	.19
BENZO(A)PYRENE	ND	.94	.19
BENZO(B)FLUORANTHENE	ND	.94	.19
BENZO(K) FLUORANTHENE	ND	1.9	.19
BENZO(G,H,I)PERYLENE	ND	.94	.19
CHRYSENE	NO	1.9	.19
DIBENZO(A,H)ANTHRACENE	ND	.94	.19
FLUORANTHENE	ND	1.9	19
FUUORENE	ND.	1.9	.19
INDENO(1,2,3-CD)PYRENE	ND	.94	.19
NAPHTHALENE	ND	.94	.19
PHENANTHRENE	ND	.94	.19
PYRENE	MD	1.9	.19
SURROGATE PARAMETERS	% RECOVERY	QC LIMIT	
TERPHENYL-D14	61	50-130	

RL: Reporting Limit



Client : SES-TECH Date Collected: 06/01/05
Project : CAMP PENDLETON, UST SITE 14121 Date Received: 06/01/05
Batch No. : 05F010 Date Extracted: 06/06/05 15:00
Sample ID: 0003-006 Date Analyzed: 06/08/05 23:15
Lab Samp ID: F010-06 Dilution Factor: .95
Lab File ID: RFK213 Matrix : WATER
Ext Btch ID: SVF009W % Moisture : NA
Calib. Ref.: RDK196 Instrument ID : T-052

	RESULTS	ŘL.	MDL
PARAMETERS	(ug/L)	(ug/L)	(ug/L)
PARAMETERS		(49/1)	(49/1/
ACENAPHTHENE	1	. 95	.19
ACENAPHTHYLENE	.27J	.95	.19
ANTHRACENE	AD.	1.9	.19
BENZO(A)ANTHRACENE	ND	1.9	.19
BENZO(A)PYRENE	ND	.95	.19
BENZO(B)FLUORANTHENE	ND	.95	.19
BENZO(K) FLUORANTHENE	ND	1.9	.19
BENZO(G,H,I)PERYLENE	ND	, 95	.19
CHRYSENE	ND	1.9	.19
DIBENZO(A, H)ANTHRACENE	ND	.95	.19
FLUORANTHENE	ОМ	1.9	.19
FLUORENE	.364	1.9	.19
ENDENO(1,2,3-CD)PYRENE	NO	.95	.19
NAPHTHALENE	ND	.95	. 19
PHENANTHRENE	ND	.95	, 19
PYRENE	RD	1.9	, 19
SURROGATE PARAMETERS	% RECOVERY	QC LIMIT	

50-130

RL: Reporting Limit

TERPHENYL-D14



Quantitation Report (QT Reviewed)

Data File : D:\CHEMDATA\05F08\RFK213.D

Vial: 15 Acq On : 8 JUN 2005 23:15 Sample : 05F010-06 Operator: KV Inst : T052 Misc Multiplr: 1.00

MS Integration Params: RTEINT.P

Quant Time: Jun 9 12:30 2005 Quant Results File: SV52D26.RES

Quant Method: C:\HPCHEM\1\METHODS\SV52D26.M (RTE Integrator)

Title : METHOD 8270C SIM GCMS-QP5000 Last Update : Wed Apr 27 16:16:37 2005 Response via : Initial Calibration

DataAcq Meth :

Internal Standards	R.T.	QIon	Response	Conc Units	Dev(Min)
1) 1,4-Dichlorobenzene-d4 18) Phenanthrene-d10 26) Perylene-d12	3.28 8.03 12.39	152 188 264	441906 726805 508419	10.00 ng 10.00 ng 10.00 ng	0.00 -0.02 0.00
System Monitoring Compounds 25) Terphenyl-d14	9.83	244	374941	6.71 ấg	0.00
Target Compounds				•	Ovalue
<pre>11) 2-Methylnaphthalene 14) Acenaphthylene</pre>	5.38 6.25	142 152	49181 40654m	0.47 ng 0.29/ng	93
15) Acenaphthene 16) Fluorene 21) Phenanthrene	6.43 7.00 8.06	154 166 178	89852 32707m 12379m	1.08/ng 0.37/ng 0.10 ng	95
				AV 619/05	



Data File : D:\CHEMDATA\05F08\RFK213.D

Acq On : 8 JUN 2005 23:15

Sample :

: 05F010-06

Vial: 15 Operator: KV Inst : TO52 Multiplr: 1.00

Misc : MS Integration Params: RTEINT.P


Quant Time: Jun 9 12:30 2005

Quant Results File: SV52D26.RES

Method : C:\HPCHEM\1\METHODS\SV52D26.M (RTE Integrator)

Title : METHOD 8270C SIM GCMS-QP5000


Last Update : Wed Apr 27 16:16:37 2005




RFK213.D SV52D26.M

Thu Jun 09 12:30:56 2005
















Quant Results File: temp.res


Quantitation Report

Data File : D:\CHEMDATA\05F08\RFK213.D

Vial: 15 Acq On : 8 JUN 2005 23:15 Operator: KV Sample : 05F010-06 Inst : TO52 Multiplr: 1.00 Misc Quant Time: Jun 9 12:25 2005

Method : C:\HPCHEM\1\METHODS\SV52D26.M (RTE Integrator)

Title : METHOD 8270C SIM GCMS-QP5000 Last Update : Wed Apr 27 16:16:37 2005 Response via : Multiple Level Calibration





Data File : D:\CHEMDATA\05F08\RFK213.D

: 8 JUN 2005 23:15 Acq On

Sample Misc

: 05F010-06

Quant Time: Jun 9 12:29 2005

Vial: 15 Operator: KV


: TO52 Inst

Multiplr: 1.00 Quant Results File: temp.res

: C:\HPCHEM\1\METHODS\SV52D26.M (RTE Integrator)

: METHOD 8270C SIM GCMS-QP5000 Title

Last Update : Wed Apr 27 16:16:37 2005 Response via : Multiple Level Calibration





Data File : D:\CHEMDATA\05F08\RFK213.D

Acq On : 8 JUN 2005 23:15

Sample : Misc :

: 05F010-06


Vial: 15 Operator: KV Inst : TO52 Multiplr: 1.00

Quant Time: Jun 9 12:29 2005

Quant Results File: temp.res

Method : C:\HPCHEM\1\METHODS\SV52D26.M (RTE Integrator)

Title : METHOD 8270C SIM GCMS-QP5000 Last Update : Wed Apr 27 16:16:37 2005 Response via : Multiple Level Calibration





Data File : D:\CHEMDATA\05F08\RFK213.D

Acq On : 8 JUN 2005 23:15

Sample Misc

: 05F010-06

Quant Time: Jun - 9 12:30 2005

Vial: 15


Operator: KV Inst : TO52

Multiplr: 1.00

Quant Results File: temp.res

: C:\HPCHEM\1\METHODS\SV52D26.M (RTE Integrator)

Title : METHOD 8270C SIM GCMS-QP5000 Last Update : Wed Apr 27 16:16:37 2005 Response via : Multiple Level Calibration





Data File : D:\CHEMDATA\05F08\RFK213.D

Acq On : 8 JUN 2005 23:15

Sample : 05

: 05F010-06

Misc : Quant Time: Jun 9 12:30 2005 Vial: 15


Operator: KV Inst : TO52

Multiplr: 1.00

Quant Results File: temp.res

Method : C:\HPCHEM\1\METHODS\SV52D26.M (RTE Integrator)
Title : METHOD 8270C SIM COMS OPERAGO

Title : METHOD 8270C SIM GCMS-QP5000 Last Update : Wed Apr 27 16:16:37 2005 Response via : Multiple Level Calibration





Multiplr: 1.00

Quantitation Report

Data File : D:\CHEMDATA\05F08\RFK213.D


į į.

Vial: 15 : 8 JUN 2005 23:15 Operator: KV Sample : 05F010-06 Inst : TO52 Misc

Quant Time: Jun 9 12:30 2005 Quant Results File: temp.res

: C:\HPCHEM\1\METHODS\SV52D26.M (RTE Integrator)

Title : METHOD 8270C SIM GCMS-QP5000 Last Update : Wed Apr 27 16:16:37 2005 Response via : Multiple Level Calibration





1.1

Client : SES-TECH Date Collected: 06/01/05
Project : CAMP PENDLETON, UST SITE 14121 Date Received: 06/01/05

 Batch No. : 05F010
 Date
 Extracted: 06/06/05 15:00

 Sample ID: 0003-007
 Date
 Analyzed: 06/08/05 23:37

 Lab Samp ID: F010-07
 Dilution Factor: .99

 Lab File ID: RFK214
 Matrix : WATER

 Ext Btch ID: SVF009W
 % Moisture : NA

 Calib. Ref.: RDK196
 Instrument ID : T-052

.

PARAMETERS	RESULTS	RL	MDL
PARAMETERS	(ug/t)	(ug/L)	(ug/L)
ACENAPHTHENE	.88J	.99	.2
ACENAPHTHYLENE	.24J	.99	.2
ANTHRACENE	ND	2	.2
BENZO(A)ANTHRACENE	ND	2	.2
BENZO(A)PYRENE	ND	.99	.2
8ENZO(B)FLUORANTHENE	ND	.99	.2
8ENZO(K)FLUORANTHENE	ND	2	.2
BENZO(G,H,I)PERYLENE	ND	.99	.2
CHRYSENE	ND	2	.2
DIBENZO(A,H)ANTHRACENE	ND	.99	.2
FLUORANTHENE	NO	2	.2
FLUGRENE	.273	S	.2
INDENO(1,2,3-CD)PYRENE	ND	,99	.2
NAPHTHALENE	ND	.99	.2
PHENANTHRENE	ND	.99	. 2
PYRENE	ND	2	.2
SURROGATE PARAMETERS	% RECOVERY	QC LIMIT	
**********	- * * - * - * 4		
TERPHENYL-D14	60	50-130	

RL: Reporting Limit



QC SUMMARIES



Client : SES-TECH Date Collected: NA Project : CAMP PENDLETON, UST SITE 14121 Date Received: 06/06/05 Batch No. : 05F010 Date Extracted: 06/06/05 15:00 Sample ID: MBLK1W Date Analyzed: 06/08/05 20:01 Lab Samp ID: SVF009WB Dilution Factor: 1 Lab file ID: RFK204 Matrix : WATER % Moisture : NA Ext Btch ID: SVF009W Catib. Ref.: RDK196 Instrument ID : T-052

	RESULTS	RL	MDL
PARAMETERS	(ug/L)	(ug/L)	(ug/L)
ACENAPHTHENE	ND	. 1	.2
ACENAPHTHYLENE	ND	1	.2
ANTHRACENE	ND	2	.2
BENZO(A)ANTHRACENE	ND	2	.2
BENZO(A)PYRENE	ND	1	.2
BENZO(B)FLUORANTHENE	ND	1	.2
BENZO(K)FLUORANTHENE	ND	2	.2
BENZO(G,H,I)PERYLENE	ND	1	.2
CHRYSENE	ND	2	.2
OIBENZO(A, H)ANTHRACENE	ND	1	.2
FLUORANTHENE	ND	2	.2
FLUORENE	GN	2	.2
INDENO(1,2,3-CD)PYRENE	ND	1	.2
NAPHTHALENE	ND	1	.2
PHENANTHRENE	ND	**	.2
PYRENE	ND	2	.2

SURROGATE PARAMETERS	% RECOVERY	QC LIMIT
/ > > > 2		
TERPHENYL-D14	84	50-130

RL: Reporting Limit



EMAX QUALITY CONTROL DATA LCS/LCD ANALYSIS

CLIENT:

SES-TECH

PROJECT:

CAMP PENDLETON, UST SITE 14121

BATCH NO.: METHOD:

05F010 SW 3520C/8270C SIM

MATRIX:

WATER

% MOISTURE:

NA

DILUTION FACTOR: 1

SAMPLE ID:

MBLK1W

SVF009WL

SVF009WC

LAS SAMP ID: LAB FILE ID:

SVF009WB RFK204

RFK205

RFK206

DATE EXTRACTED: 06/06/0515:00 06/06/0515:00 06/06/0515:00

DATE COLLECTED: NA DATE RECEIVED: 06/06/05

DATE ANALYZED: 06/08/0520:01 06/08/0520:23 06/08/0520:44 PREP. BATCH:

SVF009W

SVF009W

SVF009W

CALIB. REF:

RDK196

RDK 196

RDK196

ACCESSION:

PARAMETER	BLNK RSLT (ug/L)	SPIKE AMT (ug/L)	BS RSLT (ug/L)	8S % REC	SPIKE AMT (ug/L)	8SD RSLT (ug/L)	BSD % REC	RPD (%)	QC LIMIT	MAX RPD
A	ND	10	3.64	36*	10	4.79	48	27	40-130	30
Acenaphthene										
Acenaphthylene	ND	10	3.87	39*	10	5.15	51	28	40-130	30
Anthracene	ND	10	5.08	51	10	5.68	57	11	50-130	30
Senzo(a)anthracene	ИD	10	6.78	68	10	7.18	72	6	50-1 3 0	30
Benzo(a)pyrene	ND	10	7.02	79	10	7.35	74	5	50-130	30
Benzo(b)fluorantheme	ND	10	7.37	74	10	7.54	75	2	50-130	30
Senzo(k)fluoranthene	ND	10	6.9	69	10	7.42	74	7	30-150	30
Benza(g,h,i)perylene	ND	10	6.36	64	10	6.58	66	3	50-130	30
Chaysene	ND	10	7.32	73	10	7,79	78	6	50-130	30
Dibenzo(a,h)anthracene	NĐ	10	6.04	60	10	6.3	63	4	40-140	30
Fluoranthene	ND	10	6.02	60	10	6.26	63	4	50-130	30
fluorene	ND	10	4.3	43	10	5.49	55	24	40-130	30
Indeno(1,2,3-cd)pyrene	ND	10	5.41	54	10	5.76	58	6	30-140	30
Naphthalene	ND	10	3.41	34	10	4.48	45	27	30-130	30
Phenanthrene	ND	10	4.7	47	10	5.39	54	14	40-130	30
Pyrene	DM	10	5.96	60	10	6.32	63	6	40-130	30

	SPIKE AMT	BS RSLT	BS	SPIKE AMT	BSD RSLT	BSD	QC LIMIT
SURROGATE PARAMETER	(ug/L)	(ug/L)	% REC	(ug/L)	(ug/L)	% REC	(%)
Terphenyl-d14	10	7.2	72	10	7.06	71	50-130



LABORATORY REPORT FOR

SES-TECH

CAMP PENDLETON, UST SITE 14121

METHOD 5030B/M8015 TOTAL PETROLEUM HYDROCARBONS BY PURGE AND TRAP

SDG#: 05F010



CASE NARRATIVE

CLIENT:

SES-TECH

PROJECT:

CAMP PENDLETON, UST DITE 14121

SDG:

05F010

METHOD 5030B/M8015 TOTAL PETROLEUM HYDROCARBONS BY PURGE AND TRAP

Five (5) water samples were received on 06/01/05 for Total Petroleum Hydrocarbons by Purge and Trap analysis by Method 5030B/M8015 in accordance with SW846 3rd Edition.

1. Holding Time

Analytical holding time was met. Water samples were preserved.

2. Calibration

Initial calibrations were seven points. %RSD's were within 20%. Continuing calibrations were carried out at 12-hour intervals. All recoveries were within 85-115%.

3. Method Blank

Method blank was free of contamination at half of the reporting limit.

4. Surrogate Recovery

All recoveries were within QC limits.

5. Lab Control Sample/Lab Control Sample Duplicate

All recoveries were within QC limits.

6. Matrix Spike/Matrix Spike Duplicate

No sample was spiked.

7. Sample Analysis

Samples were analyzed according to the prescribed QC procedures. All criteria were met. Results were quantified from C_6 to C_{10} using GRO (C_6 - C_{10}) calibration factor.

LAB CHRONICLE
TOTAL PETROLEUM HYDROCARBONS BY PURSE AND TRAP

	CAMP PENDLETON, UST SITE 14121	14 14 14	14 14 14 14 14 14		11 11 11 11 11 11 11 11 11 11 11 11 11	## ## ## ## ## ## ## ## ## ## ## ## ##		SDG NO. Instrumen	SDG NO. : 05F010 Instrument ID : GCT039
					WATER				
	Laboratory	Dilution	*	Analysis	Extraction	Sample	Calibration Prep.	n Prep.	
mple ID	Sample ID	Factor	Moist	Datelime	Datelime	Data FN	Data FN	Batch	Notes
,	, , , , , , , , , , , , , , , , , , , ,	1 1 1	1 1	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 1 1 1 1 1 1 1 1		1 1 1 1 1 1		
	VA39F04B		NA	06/06/0513:11	05/06/0513:11	EF06004A	EF06002A	VA39F04	Method Blank
	VA39F04L	•	K.	06/06/0513:47	06/06/0513:47	EF06005A	EF06002A	VA39F04	lab Control Sample (1CS)
	VA39F04C	-	Α×	06/06/0514:23	06/06/0514:23	EF06006A	EF06002A	VA39F04	ICS Duplicate
	F010-03	-	Ä	06/06/0517:23	06/06/0517:23	EF06011A	EF06002A	VA39F04	Field Sample
	F010-04	•	×	06/06/0517:59	06/06/0517:59	EF06012A	FF06002A	VA39FD4	Field Samole
	F010-05	galase	N.	06/06/0518:36	06/06/0518:36	EF06013A	EF06002A	VA39F04	Field Sample
003-006	F010-06	*****	×	06/06/0519:12	06/06/0519:12	EF06014A	EF06002A	VA39F04	Sample Sample
	F010-07	•	2.3	0470470510.78	04.04.08530.70	F F D Z D 4 5 4	*0007011	,0106	

FN - Filename % Maist - Percent Moisture

4002



SAMPLE RESULTS



METHOD 5030B/8015B TOTAL PETROLEUM HYDROCARBONS BY PURGE AND TRAP

Client : SES-TECH Date Collected: 06/01/05
Project : CAMP PENDLETON, UST SITE 14121 Date Received: 06/01/05
Batch No. : 05F010 Date Extracted: 06/06/05

 Batch No. : 05F010
 Date
 Extracted: 06/06/05 17:23

 Sample ID: 0003-003
 Date
 Analyzed: 06/06/05 17:23

Lab Samp ID: F010-03 Dilution Factor: 1
Lab File ID: EF06011A Matrix : WATER

Ext Btch ID: VA39F04 % Moisture : NA
Calib. Ref.: EF06002A Instrument ID : GCT039

 PARAMETERS
 (mg/L)
 (mg/L)
 (mg/L)

 GASOLINE
 ND
 .05
 .02

SURROGATE PARAMETERS % RECOVERY QC LIMIT
BROMOFLUOROBENZENE 98 65-135



Page 1 of 2

METHOD 8015 by FID EMAX Analytical Laboratories, Inc.

File : c:\ezchrom\chrom\ef06\ef06.011
Method : c:\ezchrom\methods\vg39c30.met
Sample ID : 05F010-03 5.0ML W


Sample ID : 05F010-03 5.0ML W Acquired : Jun 06, 2005 17:23:43 Printed : Jun 07, 2005 11:31:43

User : SERGIO

Channel A Results

#	Peak Name	Ret.Time(Min)	Area	Ave. CF	ESTD Conc. (PPB)
					~~~~~
4	1,1,1-TFT	3.308	830898.0	23231.0	35.77
6	Bromofluorobenzene	10.817	619468.0	15791.7	39.23
Gl	GASOLINE (TOTAL)		75254.0	15626.4	4.82
G2	GRO(C6-C10)		44254.0	13111.9	3.38
G3	GRO(2MP-124TMB)		26772.0	13114.6	2.04
G4	GRO (C5-C12)		75254.0	15510.5	4.85

#### c:\ezchrom\chrom\ef06\ef06.011 -- Channel A





#### METHOD 50308/8015B TOTAL PETROLEUM HYDROCARBONS BY PURGE AND TRAP

Client : SES-TECH Date Collected: 06/01/05 Date Received: 06/01/05

Date Extracted: 06/06/05 17:59 Date Analyzed: 06/06/05 17:59

Project : SES-IECH
Project : CAMP PENDLETON, UST SITE 14121
Batch No. : 05F010
Sample ID: 0003-004
Lab Samp ID: F010-04
Lab File ID: EF06012A
Ext Arch ID: VAZOER/ Dilution Factor: 1 : WATER Matrix Ext 8tch ID: VA39F04 % Moisture Calib. Ref.: EF06002A Instrument ID : GCT039

RESULTS MDL PARAMETERS (mg/L) (mg/L) (mg/L) . . . . . . . . . . GASOLINE .05 .02

SURROGATE PARAMETERS % RECOVERY QC LIMIT BROMOFLUOROBENZENE 99 65 - 135

: Reporting Limit Parameter H-C Range Gasoline C6-C10



Page 1 of 2

### METHOD 8015 by FID EMAX Analytical Laboratories, Inc.

File : c:\ezchrom\chrom\ef06\ef06.012
Method : c:\ezchrom\methods\vg39c30.met


Sample ID : 05F010-04 5.0ML W Acquired : Jun 06, 2005 17:59:52 Printed : Jun 07, 2005 11:36:51

User : SERGIO

#### Channel A Results

Ħ	Peak Name	Ret.Time(Min)	Area	Ave. CF	ESTD Conc. (PPB)
3	1,1,1-TFT	3.308	843584.0	23231.0	36.31
7	Bromofluorobenzene	10.825	625491.0	15791.7	39.61
Gl	GASOLINE (TOTAL)		245823.0	15626.4	15.73
G2	GRO (C6-C10)	-	48366.0	13111.9	3.69
G3	GRO(2MP-124TMB)		48366.0	13114.6	3.69
G4	GRO(C5-C12)		227204.0	15510.5	14.65

#### c:\ezchrom\chrom\ef06\ef06.012 -- Channel A





#### METHOD 5030B/8015B TOTAL PETROLEUM HYDROCARBONS BY PURGE AND TRAP

Client : SES-TECH Date Collected: 06/01/05 Date Received: 06/01/05

Project : CAMP PENDLETON, UST SITE 14121
Batch No. : 05F010
Sample ID: 0003-005
Lab Samp ID: F010-05 Date Extracted: 06/06/05 18:36 Date Analyzed: 06/06/05 18:36

Dilution Factor: 1

: WATER e : NA Lab File ID: EF06013A Matrix Ext 8tch ID: VA39F04 % Moisture Calib. Ref.: EF06002A Instrument 10 : GCT039

RESULTS PARAMETERS (mg/L) (mg/L) (mg/L) GASOL INE .05 .02

SURROGATE PARAMETERS % RECOVERY QC LIMIT BROMOFLUOROBENZENE 100 65 - 135

: Reporting Limit Parameter H-C Range Gasoline C6-C10



Page 1 of 2

### METHOD 8015 by FID EMAX Analytical Laboratories, Inc.

File : c:\ezchrom\chrom\ef06\ef06.013
Method : c:\ezchrom\methods\vg39c30.met


Sample ID : 05F010-05 5.0ML W Acquired : Jun 06, 2005 18:36:03 Printed : Jun 07, 2005 11:40:05

User : SERGIO

#### Channel A Results

#	Peak Name	Ret.Time(Min)	Area	Ave. CF	ESTD Conc. (PPB)
		and the same time that the same and the same time and		~	
7	1,1,1-TFT	3.317	870458.0	23231.0	37.47
11	Bromofluorobenzene	10.825	630464.0	15791.7	39.92
G1	GASOLINE (TOTAL)		141212.0	15626.4	9.04
G2	GRO(C6-C10)		31673.0	13111.9	2.42
G3	GRO(2MP-124TMB)		31673.0	13114.6	2.42
G4	GRO(C5-C12)		82238.0	15510.5	5.30

#### c:\ezchrom\chrom\ef06\ef06.013 -- Channel A





### METHOD 50308/80158 TOTAL PETROLEUM HYDROCARBONS BY PURGE AND TRAP

 Sample
 ID:
 0003-006
 Date
 Analyzed:
 06/06/05
 19:12

 Lab Samp
 ID:
 F010-06
 Dilution Factor:
 1

 Lab File
 ID:
 EF06014A
 WATER

 Ext Btch
 10:
 VA39F04
 % Moisture
 : NA

 Calib.
 Ref.:
 EF06002A
 Instrument
 ID:
 GCT039

 PARAMETERS
 RESULTS (mg/L) (mg/L) (mg/L)

 GASOLINE
 ND ,05 ,02

SURROGATE PARAMETERS % RECOVERY QC LIMIT
BROMOFLUOROBENZENE 102 65-135

RL : Reporting Limit Parameter H-C Range Gasoline C6-C10



Page 1 of 2

# METHOD 8015 by FID EMAX Analytical Laboratories, Inc.

File : c:\ezchrom\chrom\ef06\ef06.014 Method : c:\ezchrom\methods\vg39c30.met


Sample ID : 05F010-06 5.0ML W
Acquired ..: Jun 06, 2005 19:12:10
Printed : Jun 07, 2005 11:42:47

User : SERGIO

#### Channel A Results

Ħ	Peak Name	Ret.Time(Min)	Area	Ave. CF	ESTD Conc. (PPB)
7	1,1,1-TFT	3.317	866595.0	23231.0	37.30
11	Bromofluorobenzene	10.817	646960.0	15791.7	40.97
Gl	GASOLINE (TOTAL)		3856333.0	15626,4	246.78
G2	GRO(C6-C10)		85134.0	13111.9	6.49
G3	GRO(2MP-124TMB)		61013.0	13114.6	4.65
G4	GRO (C5-C12)		1308423.0	15510.5	84.36

#### c:\ezchrom\chrom\ef06\ef06.014 -- Channel A





#### METHOD 50308/80158 TOTAL PETROLEUM HYDROCARBONS BY PURGE AND TRAP

Date Collected: 06/01/05 Date Received: 06/01/05 Client : SES-TECH

Project : CAMP PENDLETON, UST SITE 14121 Batch No. : 05F010 Sample ID: 0003-007 Date Extracted: 06/06/05 19:48 Date Analyzed: 06/06/05 19:48 Lab Samp ID: F010-07 Dilution Factor: 1 Lab File ID: EF06015A Matrix

Matrix : WATER % Moisture : NA Instrument ID : GCT039 Calib. Ref.: EF06002A 

RESULTS PARAMETERS (mg/L)(mg/L) (mg/L) -----GASOLINE ND .05

SURROGATE PARAMETERS % RECOVERY QC LIMIT BROMOFLUOROBENZENE 95 65-135

: Reporting Limit ameter H-C Range Parameter Gasoline C6-C10

Ext Btch ID: VA39F04



Page 1 of 2

## METHOD 8015 by FID EMAX Analytical Laboratories, Inc.

File : c:\ezchrom\chrom\ef06\ef06.015
Method : c:\ezchrom\methods\vg39c30.met


Sample ID : 05F010-07 5.0ML W Acquired :: Jun 06, 2005 19:48:13 Printed :: Jun 07, 2005 11:46:22

User : SERGIO

## Channel A Results

#	Peak Name	Ret.Time(Min)	Area	Ave. CF	ESTD Conc. (PPB)
4	1,1,1-TFT	3.317	806160.0	23231.0	34.70
11	Bromofluorobenzene	10.817	598060.0	15791.7	37.87
G1	GASOLINE (TOTAL)		4437532.0	15626.4	283.98
G2	GRO(C6-C10)		139319.0	13111.9	10.63
G3	GRO(2MP-124TMB)		104003.0	13114.6	7.93
G4	GRO (C5-C12)		1620746.0	15510.5	104.49

## c:\ezchrom\chrom\ef06\ef06.015 -- Channel A





# QC SUMMARIES



## METHOD 5030B/8015B TOTAL PETROLEUM HYDROCARBONS BY PURGE AND TRAP

Client : SES-TECH Date Collected: NA

Client : SES-TECH Date Collected: NA
Project : CAMP PENDLETON, UST SITE 14121 Date Received: 06/06/05

Lab Samp ID: VA39F04B Dilution Factor: 1
Lab File ID: EF06004A Matrix : WATER
EXt Btch ID: VA39F04 % Moisture : NA
Calib. Ref.: EF06002A Instrument ID : GCT039

 PARAMETERS
 RESULTS (mg/L) (mg/L) (mg/L)
 MD

 GASCLINE
 ND
 .05
 .02

SURROGATE PARAMETERS % RECOVERY QC LIMIT
BROMOFLUOROBENZENE 95 65-135

RL: Reporting Limit
Parameter H-C Range
Gasoline C6-C10



## EMAX QUALITY CONTROL DATA LCS/LCD ANALYSIS

CLIENT: PROJECT: SES-TECH

CAMP PENDLETON, UST SITE 14121

1

BATCH NO.:

05F010

METHOD:

METHOD 50308/80158

MATRIX:

WATER

% MOISTURE:

DILUTION FACTOR: 1 SAMPLE ID:

LAB SAMP ID: LAB FILE ID: MBLK1W VA39F04B EF06004A

VA39F04L EF06005A

VA39F04C DATE EXTRACTED: 06/06/0513:11 06/06/0513:47

1

EF06006A 06/06/0514:23

DATE COLLECTED: NA

DATE ANALYZED: PREP. BATCH: CALIB. REF:

06/06/0513:11 VA39F04 EF06002A

VA39F04 EF06002A

06/06/0513:47

NĐ

06/06/0514:23 VA39F04 EF06002A

DATE RECEIVED: 06/06/05

ACCESSION:

PARAMETER

. - - - - - - - -Gasoline

BUNK RSLT SPIKE AMT BS RSLT (mg/L) (mg/L) (mg/L)

BS % REC

SPIKE AMT

81

SPIKE AMT

(mg/L)

.5

BSD RSLT BSD (mg/L) % REC

,414

RPD (%)

QC LIMIT MAX RPD

(%) (%)

83

65-135

SURROGATE PARAMETER Bromofiuorobenzene

SPIKE AMT (mg/L) .04

BS RSLT 85 (mg/L) .0424

(mg/L) 106

.406

(mg/L) .0369

BSD RSLT

BSD QC LIMIT % REC

(%)

65 - 135



## LABORATORY REPORT FOR

SES-TECH

CAMP PENDLETON, UST SITE 14121

METHOD 5030B/8021B VOLATILE AROMATICS BY GC

SDG#: 05F010



### **CASE NARRATIVE**

CLIENT:

**SES-TECH** 

PROJECT:

**CAMP PENDLETON, UST SITE 14121** 

SDG:

05F010

## METHOD 5030B/8021B VOLATILE AROMATICS BY GC

Seven (7) water samples were received on 06/01/05 for Volatile Aromatics by GC by Method 5030/8021B in accordance with SW846  $3^{rd}$  Edition.

## 1. Holding Time

Analytical holding time was met. Samples were preserved.

### 2. Calibration

Initial calibration was six points. %RSDs were within 20%. Continuing calibrations were carried out within 12-hour intervals. All recoveries were within 85-115%.

## 3. Method Blank

Method blank was free of contamination at the reporting limit.

## 4. Surrogate Recovery

Recoveries were within QC limits.

## 5. Lab Control Sample/Lab Control Sample Duplicate

All recoveries were within QC limits.

## 6. Matrix Spike/Matrix Spike Duplicate

No sample was spiked.

## 7. Sample Analysis

Samples were analyzed according to the prescribed QC procedures. All criteria were met. All positive results above RL were confirmed by GC/FID, for MTBE confirmed by GC/MS.

LAB CHRONICLE VOLATILE AROMATICS BY GC

								3	Instrument ID : GCT039
					anneannanannanan MATER				
Client	Laboratory	Dilution	×	Analysis	Extraction	Sample	Calibration Prep.	Prep.	
Sample ID	Sample 1D	Factor	Moist	Datelime	Datelime	Data FN	Data FN	Batch	Notes
1 1 1 1 1 1 1 1 1	6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	* * * * * * * * * * * * * * * * * * * *	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		1 1 1 1 1 1	1	
MBLK1W	VA39F04B	-	ĄN	06/06/0513:11	06/06/0513:11	EF060048	EF06003B	VA39F04	Method Blank
LCS1W	VA39F05L	τ-	¥.	06/06/0514:59	06/06/0514:59	EF060078	EF06003B	VA39F04	Lab Control Sample (LCS)
LCD1W	VA39F05C	-	N.A.	06/06/0515:35	06/06/0515:35	EF060088	EF060038	VA39F04	LCS Duplicate
0003-001	F010-01	<b>(</b> -	AM	06/06/0516:11	06/06/0516:11	EF06009B	EF060038	VA39F04	Field Sample
0003-002	F010-02	₩	A.	06/06/0516:47	06/06/0516:47	EF06010B	EF060038	VA39F04	Field Sample
0003-003	F010-03	***	A.M.	06/06/0517:23	06/06/0517:23	EF060118	EF060038	VA39F04	Field Sample
0003-004	F010-04	-	4	06/06/0517:59	06/06/0517:59	EF060128	EF06003B	VA39F04	Field Sample
0003-005	F010-05	-	×	06/06/0518:36	06/06/0518:36	EF06013B	EF06003B	VA39F04	Field Sample
0003-006	F010-06	<b>~</b>	ΝA	06/06/0519:12	06/06/0519:12	EF060148	EF06003B	VA39F04	Field Sample
0003-007	£010-07	****	42	06/06/0519-48	06/06/0519:48	FF06015R	FF060038	VAROFOL	Field Sample

FN · Filename % Moist · Percent Moisture



# SAMPLE RESULTS



#### EPA METHOD 5030B/8021B VOLATILE AROMATICS BY GC

Client : SES-TECH Date Collected: 06/01/05 Project : CAMP PENDLETON, UST SITE 14121 Date Received: 06/01/05 Batch No. : 05F010 Sample ID: 0003-001 Date Extracted: 06/06/05 16:11 Date Analyzed: 06/06/05 16:11 Lab Samp ID: F010-01 Dilution Factor: 1 tab File ID: EF06009B Matrix : WATER % Moisture : NA
Instrument ID : GCT039 Ext 8tch 10: VA39F04 Calib. Ref.: EF06003B RESULTS RL PARAMETERS (ug/L) (ug/L) (ug/L) 8ENZENE ND .5 TOLUENE ND .5 ETHYLBENZENE ND XYLENES ND 1.5 ND SURROGATE PARAMETERS % RECOVERY QC LIMIT BROMOFLUOROBENZENE 104 75-125 1,1,1-TFT 103 75-125



### EPA METHOD 5030B/8021B VOLATILE AROMATICS BY GC

Date Collected: 06/01/05 Date Received: 06/01/05 Client : SES-TECH Project : CAMP PENDLETON, UST SITE 14121 Batch No. : 05F010 Date Extracted: 06/06/05 16:47 Date Analyzed: 06/06/05 16:47 Sample 1D: 0003-002 Lab Samp ID: F010-02 Dilution Factor: 1 Matrix : WATER % Moisture : NA instrument ID : GCT039 Lab File ID: EF060108 Ext Btch ID: VA39FD4 Calib. Ref.: EF060038 RESULTS MDL PARAMETERS (ug/L) (ug/L) (ug/L)BENZENE ND .5 TOLUENE ND .5 ETHYLBENZENE ND .5 XYLENES ND 1.5 MTBE ND SURROGATE PARAMETERS % RECOVERY QC LIMIT BROMOFLUOROBENZENE 110 75-125 1,1,1-TFT 75-125 109



## EPA METHOD 5030B/80218 VOLATILE AROMATICS BY GC

<b>公司以及印度中口在台灣中市的政策或指示及所以共享的共享的中国的政策以及和共和共</b>	
Client : SES-TECH	Date Collected: 06/01/05
Project : CAMP PENDLETON, UST SITE 1	4121 Date Received: 06/01/05
Batch No. : 05F010	Date Extracted: 06/06/05 17:23
Sample ID: 0003-003	Date Analyzed: 06/06/05 17:23
Lab Samp ID: F010-03	Dilution Factor: 1
Lab File ID: EF06011B	Matrix : WATER
Ext Btch ID: VA39F04	% Moisture : NA
Calib. Ref.: EF06003B	Instrument ID : GCT039
	中国中国共和共和共和共和共和共和共和共和共和共和共和共和共和共和共和共和共和共和
	RESULTS RL MDL
PARAMETERS	(ug/l) (ug/l) (ug/l)
Property and the second	******
BENZENE	.321 .5 .1
TOLUENE	ND .5 .1
ETHYLBENZENE	ND .5 .1
XYLENES	ND 1.5 .3
MTBE	ND 1 .5
SURROGATE PARAMETERS	% RECOVERY QC LIMIT
	*****
BROMOFLUOROBENZENE	105 75-125
1,1,1-TFT	104 75-125



# EPA METHOD 5030B/8021B VOLATILE AROMATICS BY GC

===:			==========	========
Clie	Client : SES-TECH	Date (	Collected: 06/0	1/05
Pro	Project : CAMP PENDLETON, UST S	SITE 14121 Date	Received: 06/0	1/05
Bati	Batch No. : 05F010	Date 6	xtracted: 06/0	6/05 17:59
Sam	Sample 10: 0003-004	Date	Analyzed: 06/0	6/05 17:59
Lab	Lab Samp ID: F010-04	Dilutio	on Factor: 1	
Lab	Lab File ID: EF060128	Matrix	: WATE	R,
Ext	Ext Btch ID: VA39F04	% Moist	ture : NA	
Cal	Catib. Ref.: EF06003B	Instru	ment ID : GCTO	39
###	******************			
		RESULTS	R L	MDL
PAR	PARAMETERS	(ug/L)	(ug/L)	(ug/L)
		*****		
BEN	BENZENE	.46J	.5	.1
TOL	TOLUENE	ND	.5	.1
ETH	ETHYLBENZENE	ND	.5	.1
XYL	XYLENES	.59J	1.5	.3
MTE	MTBE	ND .	1	.5
SUR	SURROGATE PARAMETERS	% RECOVERY	QC LIMIT	
BRC	BROMOFLUOROBENZENE	105		
1,1	1,1,1-TFT	106	75-125	
1				
RL:	RL: Reporting Limit			
1				



## EPA METHOD 5030B/8021B VOLATILE AROMATICS BY GC

	***************************************
Client : SES-TECH	Date Collected: 06/01/05
Project : CAMP PENDLETON, UST SITE 10	4121 Date Received: 06/01/05
Batch No. : 05F010	Date Extracted: 06/06/05 18:36
Sample 1D: 0003-005	Date Analyzed: 06/06/05 18:36
Lab Samp ID: F010-05	Dilution Factor: 1
Lab File ID: EF060138	Matrix : WATER
Ext Btch ID: VA39F04	% Moisture : NA
Calib. Ref.: EF060038	Instrument ID : GCT039
	· · · · · · · · · · · · · · · · · · ·
	RESULTS RL MDL
PARAMETERS	(ug/L) (ug/L) (ug/L)
	ND .5 .1
BENZENE	
TOLUENE	
ETHYLBENZENE	_
XYLENES	
MTBE	ND 1 .5
SURROGATE PARAMETERS	% RECOVERY QC LIMIT
	******
BROMOFLUOROBENZENE	108 75-125
1,1,1-TFT	108 75-125



### EPA METHOD 5030B/8021B VOLATILE AROMATICS BY GC

Date Collected: 06/01/05 Date Received: 06/01/05 Client : SES-TECH Project : GAMP PENDLETON, UST SITE 14121
Batch No. : 05F010
Sample ID: 0003-006
Lab Samp ID: F010-06
Lab File ID: EF060148 Date Extracted: 06/06/05 19:12 Date Analyzed: 06/06/05 19:12 Dilution Factor: 1 Matrix : WATER % Moisture : NA instrument 10 : GCT039 Ext Btch ID: VA39F04 Calib. Ref.: EF06003B , 本本的表現的自由的表現的表現的表現的表現的表現的表現的表現的表現的理解的表現的理解的有效的表現的的理解的理解的表現的。 本述的表現的 RESULTS RL MOL PARAMETERS (ug/L) (ug/L)(ug/L)BENZENE .41J .5 TOLUENE ND .5 ETHYLBENZENE ₩D .5 XYLENES ND 1.5 MTBE ND SURROGATE PARAMETERS % RECOVERY QC LIMIT

108

109

75 - 125

75-125

RL: Reporting Limit

BROMOFLUOROBENZENE

1,1,1-TFT



Page 2 of 2

# METHOD 8021 by PID EMAX Analytical Laboratories, Inc.


File : c:\ezchrom\chrom\ef06\ef06.014
Method : c:\ezchrom\methods\vg39c30.met

Sample ID : 05F010-06 5.0ML W
Acquired : Jun 06, 2005 19:12:10
Printed : Jun 07, 2005 11:42:47

User : SERGIO

### Channel B Results

#	Peak Name	Ret.Time(Min)	Area	Ave. CF	ESTD Conc. (PPB)
~ ~	MTBE	1.450	0.0	0.0	0.00
1	Benzene	2.383	9299.0	22516.2	0.41
3	1,1,1-TFT	3.317	591235.0	13499.4	43.80
	Toluene	5.100	0.0	0.0	0.00
	Chlorobenzene	8.400	0.0	0.0	0.00
	Ethylbenzene	8.917	0.0	0.0	0.00
	M/P-Xylenes	9.200	0.0	0.0	0.00
	O-Xylene	9.908	0.0	0.0	0.00
4	Bromofluorobenzene	10.817	1395853.0	32311.8	43.20
7	1,3-Dichlorobenzene	13.183	33948.0	30849.1	1.10
8	1,4-Dichlorobenzene	13,383	19554.0	38367.2	0.51
9	1,2-Dichlorobenzene	14.050	68521.0	26365.0	2.60





### EPA METHOD 5030B/8021B VOLATILE AROMATICS BY GC

Client : SES-TECH Date Collected: 06/01/05 Project : CAMP PENDLETON, UST SITE 14121 Batch No. : 05F01Q Date Received: 06/01/05 Date Extracted: 06/06/05 19:48 Sample 10: 0003-007 Date Analyzed: 06/06/05 19:48 Lab Samp ID: F010-07 Dilution Factor: 1 Lab File ID: EF060158 : WATER Matrix Ext Btch ID: VA39F04 % Moisture Calib. Ref.: EF060038 Instrument ID : GCT039 RESULTS MDL PARAMETERS (ug/L) (ug/L) (ug/L)BENZENE .39₫ .5 TOLUENE .243 .5 ETHYLBENZENE ND .5 XYLENES .36J 1.5 MTBE ND SURROGATE PARAMETERS % RECOVERY QC LIMIT BROMOFLUOROBENZENE 105 75-125 1,1,1-TFT 101 75-125



# QC SUMMARIES



## EPA METHOD 5030B/8021B VOLATILE AROMATICS BY GC

********	-20-22-22-22-22	*******	*******	****		******
Client : Project : Batch No. : Sample ID: Lab Samp ID: Lab File ID: Ext Btch ID: Calib. Ref.:	CAMP PENDLETON, 05F010 MBLK1W VA39F04B EF06004B VA39F04	UST SITE	14121	Date Date Date Dilut Matri % Moi		06/06/05 06/06/05 13:11 06/06/05 13:11 1 WATER NA
PARAMETERS		=======================================		ug/L)	RL (ug/L)	MDL (ug/L)
BENZENE TOLUENE ETHYLBENZENE XYLENES MTBE	e.		~	ND ND ND NO ND	.5 .5 .5 1.5	.1 .1 .3 .5
SURROGATE PAR BROMOFLUOROBE 1,1,1-TET			% RECO	101 102	9C LIMIT 75-125 75-125	



### EMAX QUALITY CONTROL DATA LCS/LCD ANALYSIS

CLIENT: PROJECT:

SES-TECH

CAMP PENDLETON, UST SITE 14121

BATCH NO.:

05F010

METHOD:

EPA METHOD 5030B/8021B

MATRIX: WATER

DILUTION FACTOR: 1 SAMPLE ID:

MBLK1W

VA39F04B EF060048

VA39F05L EF060078

VA39F0SC EF06008B DATE EXTRACTED: 06/06/0513:11 06/06/0514:59 06/06/0515:35

06/06/0515:35 VA39F04

% MOISTURE:

DATE COLLECTED: NA DATE RECEIVED: 06/06/05

NA

PREP. BATCH: CALIB. REF:

LAB SAMP ID:

LAB FILE ID:

DATE ANALYZED: 06/06/0513:11 06/06/0514:59 VA39F04 EF06003B

VA39F04 EF060038 EF06003B

ACCESSION:

PARAMETER	BLNK RSLT (ug/l)	SPIKE AMT (ug/L)	BS RSLT (ug/L)	BS % REC	SPIKE AMT (ug/L)	BSD RSLT (ug/L)	BSD % REC	RPD (%)	QC LIMIT	MAX RPD
Benzene	ND	40	39.5	99	40	41.4	104	5	75 - 125	20
Toluene	NO	40	39.2	98	40	41.1	103	5	75-125	20
Ethylbenzene	ND	40	37.7	94	40	39.4	98	4	75-125	20
Xylenes	ND	120	114	95	120	119	99	5	75-125	20
MTBE	ND	40	39.2	98	40	40.6	102	4	75-125	20

SURROGATE PARAMETER	SPIKE AMT	BS RSLT (ug/L)	BS % REC	SPIKE AMT	BSD RSLT (ug/L)	BSD % REC	QC LIMIT
Bromofluorobenzene	40	37.5	94	40	39.2	98	75 - 125
1,1,1-TFT	48	36.9	92	40	38.5	96	75 - 125



## LABORATORY REPORT FOR

SES-TECH

CAMP PENDLETON, UST SITE 14121

METHOD 3520C/M8015 TOTAL PETROLEUM HYDROCARBONS BY EXTRACTION

SDG#: 05F010



### **CASE NARRATIVE**

CLIENT:

SES-TECH

PROJECT:

**CAMP PENDLETON, UST SITE 14121** 

SDG:

05F010

## METHOD 3520C/M8015 TOTAL PETROLEUM HYDROCARBONS BY EXTRACTION

Six (6) water samples were received on 06/01/05 for Total Petroleum Hydrocarbons by Extraction analysis by Method 3520C/M8015 in accordance with SW846 3RD Edition.

## 1. Holding Time

Analytical holding time was met. Extraction was performed on 06/02/05 and completed on 06/03/05.

## 2. Calibration

Initial calibration was seven points for Diesel. %RSDs were within 20%. Continuing calibrations were carried out at 12-hour intervals and all recoveries were within 85-115%.

## 3. Method Blank

Method blank was free of contamination at half of the reporting limit.

## 4. Surrogate Recovery

All recoveries were within QC limits.

## 5. Lab Control Sample/Lab Control Sample Duplicate

All recoveries were within QC limits.

## 6. Matrix Spike/Matrix Spike Duplicate

No sample was designated for MS/MSD.

## 7. Sample Analysis

Samples were analyzed according to the prescribed QC procedures. All criteria were met. Samples were quantitated from C10 to C24 using Diesel (C10-C24) calibration factor.

Samples F010-03 to -07 displayed heavier fuel pattern.



LAB CHRONICLE TOTAL PETROLEUM HYDROCARBONS BY EXTRACTION

	יו ברש							SDG NO.	: 05F010
Project	: CAMP PENDLETON, UST SITE	SITE 14121						Instrum	ent 10
	化甲基苯酚 化二苯甲苯甲苯甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲甲	***************************************	11 11 11 11 11 11 11 11 11 11 11 11 11						+**************************************
					WATER				
Client	Laboratory	Dilution	3≪	Analysis	Extraction	Sample	Calibration Prep.	n Prep,	
Sample 10	Sample 1D	Factor	Moist	Datelime	DateTime	Data FN	Data FN	Batch	Notes
1 4 2 5 6 6 6 7 4	1 1 1 5 5 5 1 4 4	1 1	1 1	1 1 1 1 1 1 1 1 1 1 1 1				E	
MBLK 1x	DSF004WB	•	Ä	06/03/0516:08	06/02/0516:00	8F03D03A	8F030024	NYOU SE	Mothod Blank
LCS1#	DSF004M	-	ĄN	06/03/0516:51	06/82/0516:00	RED30068	BE030024	DSEDOVA	tob Control Samuel
1001	J670U35U	*	*	26 (03 601 37	00 0 0 00 00 00			K	דפה בחונותו משוחום ור
600 5000	) # too ???	_	ď.	00/03/0317:35	06/02/0516:00	BF03005A	BF03002A	DSF004W	LCS Duplicate
200-5000	F010-02	8.	¥¥	06/03/0519:03	06/02/0516:00	BF03007A	BF03002A	DSF004N	Field Sample
0003-003	F010-03	. 56.	××	06/03/0519:47	06/02/0516:00	RENZUNR	REDZODZA	nyuussu	Company of the state of the sta
0003-004	F010-04	66	**C	06/03/0520:31	06/02/0516-00	AF03000	RE03002A	##00/50	Siold Sample
0003-005	F010-05	ò	AX.	06/03/0521-15	06.402.0516.00	DE02010A	0.00000	# CO. CO.	Diches Tale 1
0003-006	£010±04	90	*	01 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	00.001.001.00	KO OFFICE	AJOOCO JO	#100L00	Field sample
F00 F000	10 10 10 10 10 10 10 10 10 10 10 10 10 1	2	£	65:12cn/cn/on	00/07/015:00	8F05011A	8F05002A	DSF0044	Field Sample
inn-con	F010-07	.65	ž	06/03/0522:43	06/02/0516:00	8F038124	8E030028	170035G	Siple Cample

FN - Filename % Moist - Percent Moisture

**5**002



# SAMPLE RESULTS



## METHOD 3520C/80158 TOTAL PETROLEUM HYDROCARBONS BY EXTRACTION

Client : SES-TECH Date Collected: 06/01/05 Project : CAMP PENDLETON, UST SITE 14121 Date Received: 06/01/05

 Batch No. : 05F010
 Date Extracted: 06/02/05 16:00

 Sample ID: 0003-002
 Date Analyzed: 06/03/05 19:03

 Lab Samp ID: F010-02
 Dilution Factor: .96

Lab Samp ID: F010-02 Dilution Factor: .96
Lab File ID: BF03007A Matrix : WAYER
Ext Btch ID: DSF004W % Moisture : NA
Calib. Ref.: BF03002A Instrument ID : GCT072

 PARAMETERS
 (mg/L)
 (mg/L)
 (mg/L)

 DIESEL
 ND
 .096
 .024

SURROGATE PARAMETERS % RECOVERY QC LIMIT
HEXACOSANE 125 65-135

RL: Reporting Limit
Parameter H-C Range
Diesel C10-C24



Page 1 of 1

# METHOD 8015 by GC/FID EMAX Analytical Laboratories, Inc.

File : c:\ezchrom\chrom\bf03\bf03.007 Method : c:\ezchrom\methods\ds72e11.met

Sample ID : 05F010-02


: Jun 03, 2005 19:03:23 ~ : Jun 06, 2005 10:13:03 Acquired Printed

User : JANE

## Channel A Results

#	Peak Name	Ret.Time(Min)	Area	Ave. CF	ESTD Conc.(ppm)
1	Bromobenzene	5.258	163459	6406.2	25.5
	Hexacosane	13.183	373627	11957.9 1	31.2
	Diesel(TOTAL)		1427	10848.4	0.1
	Diesel(C10-C24)		1427	10797.5 1	0.1
G3	Diesel(C10-C28)		1427	10799.8	0.1

## c:\ezchrom\chrom\bf03\bf03.007 -- Channel A





### METHOD 3520C/8015B TOTAL PETROLEUM HYDROCARBONS BY EXTRACTION

Client : SES-TECH Date Collected: 06/01/05 Date Received: 06/01/05

: SESTIECH
Project : CAMP PENDLETON, UST SITE 14121
Batch No. : OSFO10
Sample ID: 0003-003 Date Extracted: 06/02/05 16:00 Date Analyzed: 06/03/05 19:47 -Lab Samp ID: F010-03 Dilution Factor: .97 Lab File 1D: BF03008A Matrix

: WATER Ext 8tch ID: DSF004W % Moisture Calib. Ref.: BF03002A Instrument ID : GCT072

RESULTS PARAMETERS (mg/L) (mg/L) (mg/L) ......... .21 / DIESEL .097 .024

SURROGATE PARAMETERS % RECOVERY QC LIMIT HEXACOSANE 119 65 - 135

: Reporting Limit Parameter H-C Range C10-C24 Dieset



Page 1 of 1

# METHOD 8015 by GC/FID EMAX Analytical Laboratories, Inc.

File : c:\ezchrom\chrom\bf03\bf03.008 Method : c:\ezchrom\methods\ds72e11.met

Sample ID : 05F010-03


Acquired : Jun 03, 2005 19:47:23 : Jun 06, 2005 11:12:38 Printed

User : JANE

## Channel A Results

#	Peak Name	Ret.Time(Min)	Area	Ave. CF	ESTD Conc. (ppm)
				****	
1	Bromobenzene	5.250	582462	6406.2	90.9
	Hexacosane	13.183	356159	11957.9	29.8
	Diesel (TOTAL)		436570	10848.4	40.2
	Diesel (C10-C24)		228494	10797.5	21.2
G3	Diesel(C10-C28)		335850	10799.8	31.1

#### c:\ezchrom\chrom\bf03\bf03.008 -- Channel A



5007



### METHOD 3520C/80158 TOTAL PETROLEUM HYDROCARBONS BY EXTRACTION

Client : SES-TECH Date Collected: 06/01/05 Date Received: 06/01/05

Utient : SES-TECH
Project : CAMP PENDLETON, UST SITE 14121
Batch No. : OSF010
Sample 10: 0003-004
Lab Samp ID: F010-04
Lab File ID: BF03009A
Ext Btch ID: DSF004W Date Extracted: 06/02/05 16:00 Date Analyzed: 06/03/05 20:31 -Dilution Factor: .99 Matrix : WATER % Moisture

Calib. Ref.: BF03002A Instrument ID : GCT072 

RESULTS (mg/L) (mg/L) (mg/L)PARAMETERS ......... .86 .099 .025 DIESEL

% RECOVERY QC LIMIT SURROGATE PARAMETERS 65-135 130 HEXACOSANE

: Reporting Limit ameter H-C Range sel C10-C24 Parameter Diesel



Page 1 of 1

## METHOD 8015 by GC/FID EMAX Analytical Laboratories, Inc.

File : c:\ezchrom\chrom\bf03\bf03.009
Method : c:\ezchrom\methods\ds72el1.met =

Sample ID : 05F010-04


Acquired : Jun 03, 2005 20:31:19
Printed : Jun 09, 2005 16:50:22

User : JANE

### Channel A Results

#	Peak Name	Ret.Time(Min)	Area	Ave. CF	ESTD Conc. (ppm)
~ ~					
1	Bromobenzene	5.250_	582258	6406.2 -	90.9
	Hexacosane	13.183 -	387281	11957.9	32.4
	Diesel (TOTAL)		1865464	10848.4 -	172.0
	Diesel(C10-C24)		940430	10797.5	87.1
G3	Diesel(C10-C28)		1618361	10799.8	149.9

#### c:\ezchrom\chrom\bf03\bf03.009 -- Channel A



**5009** ∵.ઝ⊀



### METHOD 3520C/8015B TOTAL PETROLEUM HYDROCARBONS BY EXTRACTION

: SES-TECH Date Collected: 06/01/05 Date Received: 06/01/05

Project : CAMP PENDLETON, UST SITE 14121 Batch No. : 05F010 Date Extracted: 06/02/05 16:00 Sample ID: 0003-005 Lab Samp ID: F010-05 Date Analyzed: 06/03/05 21:15 -Dilution Factor: .94 : WATER Lab File ID: BF03010A Matrix Ext Btch 10: DSF004W % Moisture : NA

Calib. Ref.: BF03002A Instrument ID : GCT072 zzpetturetrenen zenen zene

RESULTS MDL PARAMETERS (mg/L) (mg/L) (mg/L) DIESEL .024 .26 .094

SURROGATE PARAMETERS % RECOVERY QC LIMIT HEXACOSANE 123 65-135

: Reporting Limit nmeter H-C Range Parameter Diesel C10-C24



Page 1 of 1

## METHOD 8015 by GC/FID EMAX Analytical Laboratories, Inc.

File : c:\ezchrom\chrom\bf03\bf03.010 Method : c:\ezchrom\methods\ds72e11.met Sample ID


: 05F010-05 : Jun 03, 2005 21:15:22 : Jun 06, 2005 10:19:18 Acquired Printed

User : JANE

## Channel A Results

#	Peak Name	Ret.Time(Min)	Area	Ave. CF	ESTD Conc. (ppm)
		~			
1	Bromobenzene	5.250	647594	6406.2 -	101.1
	Hexacosane	13.175	366582	11957.91	30,7
	Diesel (TOTAL)		740000	10848.4-	68.2
	Diesel(C10-C24)		295313	10797.5 -	27.4
G3	Diesel(Cl0-C28)		471716	10799.8 -	43.7

#### c:\ezchrom\chrom\bf03\bf03.010 -- Chennel A



5011 % (60)



## METHOD 3520C/80158 TOTAL PETROLEUM HYDROCARBONS BY EXTRACTION

Client : SES-TECH Date Collected: 06/01/05 Project : CAMP PENDLETON, UST SITE 14121 Date Received: 06/01/05

 Batch No. : 05F010
 Date Extracted: 06/02/05 16:00

 Sample ID: 0003-006
 Date Analyzed: 06/03/05 21:59 

 Lab Samp ID: F010-06
 Dilution factor: .96

 Lab File ID: BF03011A
 Matrix : WATER

 Ext Btch ID: DSF004W
 % Moisture : NA

Calib. Ref.: BF03002A Instrument ID : GCT072

 PARAMETERS
 RESULTS
 RL
 MDL

 01ESEL
 1.1
 .096
 .024

SURROGATE PARAMETERS % RECOVERY QC LIMIT
HEXACOSANE 122 65-135

RL: Reporting Limit
Parameter H-C Range
Diesel C10-C24



Page 1 of 1

## METHOD 8015 by GC/FID EMAX Analytical Laboratories, Inc.

File Method : c:\ezchrom\chrom\bf03\bf03.011
: c:\ezchrom\methods\ds72e11.met

Sample ID

: 05F010-06

Acquired

: Jun 03, 2005 21:59:20 '
: Jun 06, 2005 10:20:24


Printed

User : JANE

### Channel A Results

#	Peak Name	Ret.Time(Min)	Area	Ave, CF	ESTD Conc. (ppm)
1	Bromobenzene	5.250	540396	6406.2	84.4
15	Hexacosane	13,175	364334	11957.9 ~	30.5
	Diesel (TOTAL)		1423124	10848.4 <	131.2
G2	Diesel(C10-C24)		1185652	10797.5-	109.8
G3	Diesel(C10-C28)		1330569	10799.8	123.2

#### c:\ezchrom\chrom\bf03\bf03.011 -- Channel A





#### METHOD 3520C/80158 TOTAL PETROLEUM HYDROCARBONS BY EXTRACTION

Client: SES-TECH
Project: CAMP PENDLETON, UST SITE 14121
Batch No.: 05F010 Date Collected: 06/01/05 Date Received: 06/01/05

Sample ID: 0003-007 Lab Samp ID: F010-07

Date Received: 06/01/05
Date Extracted: 06/02/05 16:00
Date Analyzed: 06/03/05 22:43 
Dilution factor: .97
Matrix : WATER
% Moisture : NA
Instrument ID : GCT072 Lab File ID: BF03012A Ext 8tch ID: DSF004W

Calib. Ref.: BF03002A 

RESULTS RL MDL PARAMETERS (mg/L) (mg/L) (mg/t)

.097 DIESEL .024 1.1 / SURROGATE PARAMETERS QC LIMIT % RECOVERY

65 - 135 HEXACOSANE 130

: Reporting Limit Parameter H-C Range C10-C24 Diesel



Page 1 of 1

## METHOD 8015 by GC/FID EMAX Analytical Laboratories, Inc.

: c:\ezchrom\chrom\bf03\bf03.012 File Method : c:\ezchrom\methods\ds72el1.met^

Sample ID : 05F010-07


: Jun 03, 2005 22:43:21 < : Jun 06, 2005 10:21:08 Acquired Printed

User : JANE

### Channel A Results

#	Peak Name	Ret.Time(Min)	Area	Ave. CF	ESTD Conc. (ppm)
	~~~~~~~~~~~~~~~~~				
	Bromobenzene	5.250	501020	6406.2 -	78.2
14	Hexacosane	13.175	390065	11957.9~	32.6
	Diesel (TOTAL)		1422012	10848.4 -	
G2	Diesel(C10-C24)		1192110	10797.5	110.4
G3	Diesel(C10-C28)		1325371	10799.8~	122.7

c:\ezchrom\chrom\bf03\bf03.012 -- Channel A





QC SUMMARIES



METHOD 3520C/8015B TOTAL PETROLEUM HYDROCARBONS BY EXTRACTION

Date Collected: NA

Client : SES-TECH
Project : CAMP PENDLETON, UST SITE 14121
Batch No. : 05F010
Sample ID: MBLK1W'
Lab Samp ID: DSF004WB Date Received: 06/02/05
Date Extracted: 06/02/05 16:00
Date Analyzed: 06/03/05 16:08 -Dilution Factor: 1

: WATER Lab File ID: BF03003A Matrix Ext Btch ID: DSF004W % Moisture

Instrument ID : GCT072 Calib. Ref.: BF03002A

ARREST CONTROL OF COOLS AND CONTROL OF CONTR

RESULTS RL MDL (mg/L) PARAMETERS (mg/L) (mg/L) DIESEL ND . 1 .025

SURROGATE PARAMETERS % RECOVERY QC LIMIT HEXACOSANE 100 65-135

: Reporting Limit ameter H-C Range Parameter Dieset C10-C24



EMAX QUALITY CONTROL DATA LCS/LCD ANALYSIS

CLIENT:

SES-TECH

PROJECT:

SAMPLE ID:

LAB SAMP ID:

LAB FILE ID:

CAMP PENDLETON, UST SITE 14121

BATCH NO.: 05F010

METHOD:

METHOD 3520C/8015B

MATRIX: WATER

DILUTION FACTOR: 1

1

MBLK1W

DSF004WB

BF03003A

DSF004WL BF03004A DSF004WC BF03005A

DATE EXTRACTED: 06/02/0516:00 DATE ANALYZED: 06/03/0516:08 PREP. BATCH:

06/03/0516:51 DSF004W

06/02/0516:00 06/02/0516:00 06/03/0517:35 DSF004W

DATE COLLECTED: NA

% MOISTURE:

NA

CALIB. REF:

DSF004W BF03002A

BF03002A

BF03002A

DATE RECEIVED: 06/02/05

ACCESSION:

PARAMETER

BLNK RSLT SPIKE AMT (mg/L) (mg/L)

SPIKE AMT BS RSLT

% REC

SPIKE AMT

SPIKE AMT BSD RSLT (mg/L) (mg/L) 4.59

850

850 RPO % REC

(%) (%)

(%) 30

QC LIMIT MAX RPD

Dieset

Hexacosane

4.62

92

92

65-135

SURROGATE PARAMETER

(mg/L) (mg/L) % REC .25 297

88

BS RSLT

(mg/L)

(mg/L) .25

(mg/L) .303

BSD RSLT

% REC 121

QC LIMIT (%)

65-135

5018